



DANGER

May be corrosive to metals. Causes severe skin burns and eye damage.

Keep only in original container. Do not breathe mist, spray. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

Absorb spillage to prevent material-damage.

Store locked up. Store in corrosive resistant container with a resistant inner liner

⚠ WARNING: This product can expose you to ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NFPA* RATINGS

Health: 2; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5; Sodium Tripolyphosphate Anhydrous/ 7758-29-4; Sodium Metasilicate/ 6834-92-0; Sodium Laureth Sulfate/ 9004-82-4; Potassium Hydroxide/ 1310-58-3; Ethanol/ 64-17-5

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

TOTAL SOLUTIONS®

INDUSTRIAL CLEANERS
and DEGREASERS

STEAM AND PRESSURE WASH CONCENTRATE

Strips Away Dirt and Grime

- REMOVES GREASE AND OIL
- IDEAL FOR FIBERGLASS, VINYL, CONCRETE AND OTHER SURFACES

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417
PO Box 240014 • Milwaukee, WI 53224 • athea.com

DESCRIPTION

Formulated to provide fast and effective cleaning with steam cleaners, this concentrate quickly removes grime, oil, grease, road film, carbon, black streaks, and other tough soils from fiberglass, vinyl, industrial equipment, concrete, gutters, and vehicle engines.

DIRECTIONS

Adjust the feed rate of steam cleaner to obtain the dilution of 1:20-1:40. Heavy deposits may require more concentrate, and lighter deposits may require less.

Be sure to rinse the steam cleaning equipment with clean water after each use. Do not use on aluminum. Spot test first if using on painted surfaces.

DISPOSAL

Dispose of contents/container to comply with local/regional/national/international regulations.



Please Recycle.

0405.031120