



DANGER

May be corrosive to metals. Causes severe skin burns and eye damage.

Keep only in original container. Do not breathe mist, spray. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

Absorb spillage to prevent material damage.

Store locked up. Store in corrosive resistant container with a resistant inner liner.

⚠ WARNING: This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NFPA® RATINGS

Health: 2; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5; Pentasodium Triphosphate/7758-29-4; Trisodium Phosphate Dodecahydrate/10101-89-0; Potassium Hydroxide/1310-58-3; Sodium Metasilicate/6834-92-0; Phosphoric Acid/7664-38-2.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

TOTAL SOLUTIONS®

AUTOMOTIVE

TRUCK WASH

Restores Luster to Finish

- DRIES SPOTLESS AND FILM FREE
- BIODEGRADABLE

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417
PO Box 240014 • Milwaukee, WI 53224 • athea.com

DESCRIPTION: This concentrated detergent is used to remove severe soiling, road tar and grime from trucks and other large vehicles. It cleans quickly and dries spot-free and film-free to restore the original luster to the vehicle's finish. This detergent is designed for use in high-pressure washing equipment.

DIRECTIONS: For best results, wash all vehicles in a protected or shaded area - not in the hot sun. For normal cleaning, dilute 40:1 for use through standard pressure washing equipment. Severe soiling, road tar, salt residue or heavy exhaust soot may require stronger solutions or agitation.

The detergent solution may be sprayed, mopped or sponged onto wet vehicle surfaces. Allow to penetrate for several minutes, then rinse the clean surface thoroughly with water.

To avoid streaking, always wash vehicles by starting on the lower soiled parts and moving upward to the higher sections.

DISPOSAL

Dispose of contents/container to comply with local/regional/national/international regulations.



Please Recycle.

0430.091322