



DANGER

Harmful in contact with skin. Causes severe skin burns and eye damage.

Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. **IF ON SKIN:** Wash with plenty of water. **IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water/shower. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. Call a poison center or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse.

Store locked up.

DISPOSAL

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

TOTAL SOLUTIONS®

WASTEWATER and
SEWAGE TREATMENT

SUPER HIGH HEAT™

Heavy Duty Activated Alkaline
Drain Opener

• NSF REGISTERED

DESCRIPTION

This heavy duty drain opener contains caustic granules activated by aluminum needles that release substantially more intense heat and turbulence than any regular strength drain opener.

The heat and movement liquefy, dissolve and remove a variety of clogging material such as hair, paper, animal and vegetable fats and oils, as well as other organic matter that clog drains and sewer lines.

DIRECTIONS

For Municipal Sewer Lines

Pour or shovel 20 pounds of product into strategic manholes. If sewer system is dry, flush product with plenty of water.

For Industrial Drains

Pour 1-2 pounds of product down drain. Where accumulations of grease and organic matter are high, pour 3-5 pounds of product down drain.

**BE AWARE

- Generates heat that may cause hazardous liquids to erupt.
- Place a deep container over treated drain.
- Never use a plunger with this product.
- Never look directly into a treated drain.
- Never use with or immediately after acid-type drain openers.
- Never enter treated sewers until thoroughly flushed with water.

NFPA® RATINGS

Health: 3; Flammability: 0; Reactivity: 2; Special: W

CONTAINS/CAS NUMBER:

Sodium Hydroxide/1310-73-2; Sodium Nitrate/7631-99-4; Aluminum Chips/7429-90-5; Sodium Chloride/7440-23-5; Dye/Mixture

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 50 Lb Pail

Manufactured By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224
1-800-743-6417



Please Recycle.



Nonfood Compounds
Program Listed L1
Registration No. 135390

0618.073019

For industrial and commercial use only.
For additional information, see Safety Data Sheet.

Specimen Label