WARNING: This product can expose you to Ethylene Oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NFPA® RATINGS

Health: 1; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5: Sulfamic Acid/5329-14-6: Linear Alcohol Ethoxylate/34398-01-1:

Glycerin/56-81-5; Benzaldehyde/100-52-7





RESILIENT FLOOR CARE

FLOOR NEUTRALIZER

Neutralizes Detergent and Stripper Residues

 ELIMINATES BROWNING OF RUGS, CARPET AND UPHOLSTERY

• RINSES RESIDUES LEFT BY DE-ICERS

DESCRIPTION

This industrial strength rinsing compound has been developed specifically to cut through the dulling, white chalky residue left by ice melting chemicals. Salt residue is chemically dissolved without harming sensitive painted or finished surfaces.

DIRECTIONS

FOR DAILY DAMP MOPPING: Use 1-3 ounces per gallon of rinse water. Apply liberally to floor with a mop, allowing the solution to act for several minutes. Rinse immediately with clean water, wringing out mop frequently.

TO REMOVE HEAVY FILM FROM EQUIPMENT: Dilute 6 ounces per gallon of rinse water. Spray liberally over the equipment surfaces and allow to act for several minutes. Rinse with clean water.

TO ELIMINATE CARPET STAINS LEFT BY ICE MELTING RESIDUE: Use 1-3 ounces per gallon of water in carpet extraction equipment. Do not use a hot solution and do not mix this product with any other chemical.

DISPOSAL

 $\label{lem:prop:container} Dispose of contents/container to comply with local/regional/national/international regulations.$

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions[®] • 1-800-743-6417 PO Box 240014 • Milwaukee, WI 53224 • athea.com



For industrial and commercial use only. For additional information, see Safety Data Sheet.