

# MULTI-PURPOSE PENETRANT



## DANGER:

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

## FIRST AID:

**IF SWALLOWED:** Immediately call a poison center/doctor. Do NOT induce vomiting. **IF ON SKIN:** Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists. **IF IN EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists. **IF INHALED:** Move to fresh air. Call a physician if symptoms develop or persist.

## CONTAINS/CAS NUMBER:

Distillates (Petroleum), Hydrotreated light (64742-47-8), Distillates (Petroleum), Heavy Paraffinic (64742-65-0), Mineral Spirits (64742-48-9), Diethylene Glycol Monobutyl Ether (112-34-5) and Propane (74-98-6).

Distributed By: Total Solutions®  
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

See Safety Data Sheet for complete safety information. 24 HOUR MEDICAL EMERGENCY 1-866-836-8855 CONTAINS NO OZONE DEPLETING CHEMICALS!

# TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

## MULTI-PURPOSE PENETRANT

Non-Conducting up to  
21,000 Volts

- LUBRICATES
- LOOSENS NUTS AND BOLTS
- RETARDS CORROSION
- NEVER DRIES
- DISPLACES MOISTURE
- PENETRATES FASTER AND FARTHER

**KEEP OUT OF REACH OF CHILDREN**

**DANGER**

**HARMFUL OR FATAL IF SWALLOWED.**

**FLAMMABLE.**

**CONTENTS UNDER PRESSURE.**

Read carefully other cautions on back panel.

**NET WT: 15 OZ (425 g)**

Distributed By: Total Solutions®  
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

## DESCRIPTION

Saves production, maintenance, and repair time. Protects and preserves equipment. Spray on, let set and the fast-acting, penetrating formula goes to work. It loosens the rust or corrosion, making it easy to separate the surfaces. For use on refrigerator equipment, automobiles, work-shops. Free nuts and bolts. Lubricates locks, hinges, moving parts. Stops and retards corrosion. Stops corrosion on battery terminals.

## DIRECTIONS

Remove cap and point valve opening toward surface to be sprayed. Hold can 4-8 inches away, push button and spray. For stubborn cases, repeat the spray and allow to set for a few minutes.

**Cautions:** Use with adequate ventilation.

**KEEP OUT OF REACH OF CHILDREN.**

## HMIS® RATINGS:

HEALTH - 1, FLAMMABILITY - 4,  
PHYSICAL HAZARD- 0, PERSONAL  
PROTECTION - X.