

GRAPHITE LUBRICANT



DANGER: Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May cause cancer (Inhalation). May cause damage to organs through prolonged or repeated exposure. May cause genetic defects.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, open flames, sparks. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe fume, gas, mist, spray, vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash it before reuse.

IF SWALLOWED: Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting. **IF ON SKIN:** Wash with plenty of water. **If skin irritation occurs:** Get medical advice/attention. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **If exposed or concerned:** Get medical advice/attention. Call a doctor, a POISON CENTER if you feel unwell.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

DISPOSAL: Dispose of contents/container to comply with local/regional/national/international regulations.

WARNING: This product can expose you to toluene, which is known to the State of California to cause birth defects or other reproductive harm, Crystalline Silica, which is known to the State of California to cause cancer, ethylbenzene, which is known to the State of California to cause cancer, and benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

CONTAINS/CAS NUMBER: Toluene/108-88-3; Propane /74-98-6; n-Butane/106-97-8; Graphite/7782-42-5; Acrylic Polymer(s)/Proprietary; Crystalline Silica/14808-60-7; Benzene/71-43-2; Ethylbenzene/100-41-4

Distributed By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

See Safety Data Sheet for complete safety information. For industrial and commercial use only.

TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

GRAPHITE LUBRICANT

High Temperature
Dry Lubricant

- REDUCES FRICTION & PROTECTS METAL

KEEP OUT OF REACH OF CHILDREN

DANGER

Extremely flammable aerosol.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

May cause cancer (Inhalation).

May cause damage to organs through prolonged or repeated exposure.

Read carefully other cautions on back panel.

NET WT: 12 OZ (340 g)

Distributed By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

DESCRIPTION

GRAPHITE LUBRICANT lubricates with a dry thin film of graphite. It protects metal as it eliminates friction and squeaking from tools, hardware and accessories.

Unaffected by temperature fluctuations to provide superior lubrication at both high (800°F) and low (-100°F) temperature extremes.

DIRECTIONS

SHAKE WELL BEFORE USING. Hold nozzle 6 to 8 inches from surface requiring lubrication. Generously apply to surface requiring lubrication. Reapply as necessary to maintain lubrication level. Clean nozzle after each use by inverting can and spraying.

KEEP OUT OF REACH OF CHILDREN.

NFPA RATINGS:

Health: 3; Flammability: 4; Reactivity: 0