RUST CONVERTER





DANGER:

Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye/face protection. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

FIRST AID:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash off with soap and water. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse. IF SWALLOWED: Rinse mouth. Get medical attention if symptoms occur.

WARNING: This product can expose you to chemicals including Acetaldehyde, which is known to the state of California to cause Cancer, and Ethylene Glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

CONTAINS/CAS NUMBER:

Acetone (67-64-1), Dimethyl Ether (115-10-6), Isobutane (75-28-5), Ethylene Glycol (107-21-1), Isopropyl Alcohol (67-63-0), Propane (74-98-6), Tannic Acid (1401-55-4) and Oxalic Acid (144-62-7).

Distributed By: Total Solutions® PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

RUST CONVERTER

Converts Rust To Form A Stable Paintable Surface

- ELIMINATES THE NEED FOR SCRAPING, SANDBLASTING OR PRIMING RUSTY SURFACES
- PROTECTS FROM FURTHER RUSTING ON SURFACES EXPOSED TO RAIN, SUN AND SALT SPRAY

191

DESCRIPTION

When applied to any rusty surface, it will convert the residual rust to a protective polymeric coating. This inert protective coating prevents further rusting and corrosion.

DIRECTIONS

For best results prepare surface by brushing the loose rust from the surface using a wire brush or sand paper. Clean the surface to remove grease and grime. Shake well before use. Hold can 8-12 inches from surface and spray a thin coat onto the surface. After the surface has dried, it will turn black. Then apply a second thin coat. Allow 48 hours to completely cure before painting while protecting it from rain or dew.

For long lasting protection, seal with two coats of a high quality oil based paint.

Do not apply if the surface temperature is below 50°F or above 90°F. Store in a cool dry place, protected from freezing or temperatures above 100°F.

KEEP OUT OF REACH OF CHILDREN DANGER

EXTREMELY FLAMMABLE.
MAY CAUSE BURNS TO EYES, SKIN, AND
RESPIRATORY TRACT.
CONTENTS UNDER PRESSURE.

Read carefully other cautions on back panel.

NET WT: 13 OZ (369 g)

Distributed By: Total Solutions® PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

Cautions: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

HMIS® RATINGS:

HEALTH - 2, FLAMMABILITY - 3, PHYSICAL HAZARD- 2, PERSONAL PROTECTION - X.

See Safety Data Sheet for complete safety information. 24 HOUR MEDICAL EMERGENCY 1-866-836-8855 CONTAINS NO OZONE DEPLETING CHEMICALS!

8346.061818