

# Oxy Treat

Product # 0927

*Prevents oxygen pitting in steam boilers*

This liquid is a catalyzed oxygen scavenger that quickly removes dissolved oxygen from boiler feedwater. It also provides additional protection against pitting and corrosion of internal boiler surfaces when used in conjunction with scale and corrosion inhibitors. Plus, it can be mixed with other treatment products and fed into the feedwater system, or fed directly into the boiler.

## Steam Boiler & Closed Loop Treatment That Is Effective Against

- Corrosion
- Rust

## Features and Benefits

- Quickly attacks dissolved oxygen in boiler-feed water before it becomes in contact with metal surfaces.
- Can be safely used in boiler systems with our without a deaerator.
- Is effective in both steam boilers and closed loop recirculating systems.

## Properties

Appearance	Pink Liquid
Fragrance	Sulfur
Concentrate	Yes
Specific Gravity	1.17
pH	6.0 – 7.0

## Directions

*Complete directions on product label*  
Recommended for use with a continuous feed system to maintain a sulfite level between 20 - 40 ppm.

## Ingredients

Water  
Sodium Metabisulfite  
Sodium Sulfite  
Sodium Sulfate  
Cobalt monosulfate heptahydrate

## CAS Number

7732-18-5  
7681-57-4  
7757-83-7  
7757-82-6  
10026-24-1

## Safety

DANGER: Causes serious eye damage.

## DOT Shipping (Ground Transportation)

Proper Shipping Name	None
Class	None
ID Number	None
Packing Group	None

## Quantities

30, 35 & 55 gallon  
5 or 6 gallon  
6 X 1 gallon  
4 X 1 gallon

## NFPA® RATINGS

