Safety Data Sheet Blue Silica Nanoparticles in H₂O

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Blue Silica Nanoparticles in H₂O, 20nm – 200nm Silica

Nanoparticles in H₂O.

COMMON SYNONYMS: Blue Silicon Dioxide nanoparticles dispersed in De-ionized

water, methylene blue silica, colloidal silica, amorphous

silica

CHEMICAL FAMILY: Silicon Compounds

FORMULA: Methylene Blue dyed SiO₂ dispersed in H₂O

Identified uses: Laboratory chemical, Manufacture of substances

Supplier: General Engineering & Research, L.L.C.

10459 Roselle St. Ste. A San Diego, CA 92121-1527

Information: 858-291-8336

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

OSHA Hazards: Inhalation of mist or dust may be harmful. Avoid repeated or prolonged breathing of spray mist or dust.

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Specific target organ toxicity – repeated exposure (Category 1), H372 For the full text of the H-Statement mentioned in the Section, see Section 16.

2.2 GHS Label elements, including precautionary statements





Pictogram

Signal word Danger

Hazard statement(s)

H372 Causes damage to organs through prolonged or repeated exposure.

H302 Harmful if swallowed.

Precautionary statement(s)

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Get medical advice/ attention if you feel unwell.

Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Component | Cas-No. | Concentration |
|---------------------------|------------------------|------------------|
| Water Colloidal Silica | 7732-18-5 7631-86-9 | >80.0% <15.0% |
| Methylene Blue | 122965-43-9 | <0.1% |

Appearance

Form Liquid Colour blue Odour none

3.1 Substances

Formula: O₂Si

Molecular weight: 60.08 g/mol Cas-No.: 7631-86-9

Formula: C16H18CIN3.xH2O

Molecular weight: 319.85 g/mol Cas-No.: 200-515-2

| Hazardous Component | Classification | Concentration |
|-----------------------------|--------------------|---------------|
| Silicon dioxide (amorphous) | STOT RE 1: H372 | <15% |
| Methylthioninium chloride | Acute Tox. 4; H302 | <0.1% |
| hydrate A | | |

For the full text of H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in Section 2.

4.3 Indication of any immediate medical attention and special treatment needed No data available

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

silicon oxides, carbon oxides, nitrogen oxides (NOx), sulphur oxides, hydrogen chloride gas

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Avoid breathing dust. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

Handling

Use only well ventilated areas. Avoid contact with eyes. Avoid contact with skin, inhalation and ingestion. Avoid breathing vapor. Avoid breathing dust. Keep from freezing. Keep away from children. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Storage

Storage conditions: Keep container tightly closed in a dry and well-ventilated place. Storage class (TRGS 510): Non Combustible Solids

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits(s)

Exposure limits are listed below, if they exist.

| Component | CAS-No. | Value | Control parameters | Basis |
|-----------|----------|--|--------------------|-----------------------------------|
| Silicon | 7631-86- | TWA | 6.0 mg/m3 | USA. NIOSH Recommended |
| dioxide | 9 | | | Exposure Limits |
| | | TWA | 20.0 Million | USA. Occupational Exposure Limits |
| | | | particles per | (OSHA) – Table Z-3 Mineral Dusts |
| | | | cubic foot | |
| | | TWA | 80.0 mg/m3 / % | USA. Occupational Exposure Limits |
| | | | SiO2 | (OSHA) – Table Z-3 Mineral Dusts |
| | | Millions of particles per cubc foot of air, based on impinge | | |
| | | samples counted by light-field techniques. | | |
| | | mppcf X 35.3 = million particles per cubic meter = particles per | | |
| | | C.C. | | |
| Silicon | 7631-86- | TWA | 1,000 ppm | USA. ACGIH Threshold Limit Values |
| dioxide | 9 | | | (TLV) |
| | Remarks | Upper Respiratory Tract irritation | | |
| | | Confirmed animal carcinogen with unknown relevance to humans | | |
| | | TWA | 1,000ppm | USA. OHSA – TABLE Z-1 Limits for |
| | | | 1,900 mg/m3 | Air Contaminants – 1910.1000 |
| | | TWA | 1,000ppm | USA. Occupational Exposure Limits |
| | | | 1,900 mg/m3 | (OSHA) – Table Z-1 Limits for Air |
| | | | | Contaminants |

GENERAL ENGINEERING AND RESEARCH

| The value in mg/m3 is approximate | | |
|--|-----------------|-----------------------------------|
| TWA | 1,000.00000 | USA. NIOSH Recommended |
| | Ppm | Exposure Limits |
| | 1,900.00000 | |
| | Mg/m3 | |
| STEL | 1,000.00000 ppm | USA. ACGIH Threshold Limit Values |
| | | (TLV) |
| Upper Respiratory Tract irritation | | |
| Confirmed animal carcinogen with unknown relevance to humans | | |

Eye protection: Goggles

Hand protection: Nitrile rubber gloves. Other chemical resistant gloves may be

recommended by your safety professional.

Skin and body protection: Normal work wear.

Respiratory protection: No personal respiratory protective equipment normally required. The specific respirator selected must be based on the airborne concentration found in the workplace and must not exceed the working limits of the respirator.

Engineering measures: Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure, mechanical ventilation (local exhaust), and control of process conditions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form liquid
Colour blue
Odour none

pH 8.0 – 11.0

Boiling point/range similar to water
Flash point not applicable

Component: Silica

Relative vapour density Heavier than air.

Water solubility partly soluble

Relative density 1.00 – 1.20

Evaporation rate Slower than ether

VOC's 0 g/l

Note: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Hazardous reactions Stable under normal conditions

Conditions to avoid Extreme heat, freezing temperatures

Materials to avoid strong oxidizers

Products

Hazardous decomposition oxides of silicon, irritating fumes, acidic fumes. Hazardous

decomposition products formed under fire conditions. -Carbon oxides, Nitrogen oxides (NOx), Sulphur oxides,

Hydrogen chloride gas.

Polymerization Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

Component: Silica

Acute oral toxicity LD50 rat > 3,000 mg/kg

Inhalation: No data available Dermal: No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Carcinogenicity

Carcinogenicity - Rat - Inhalation

Tumorigenic: Carcinogenic by RTECS criteria. Lungs, Thorax, or Respiration: Tumors.

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Silicon dioxide)

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Aspiration hazard

No data available

Additional Information

RTECS: SP5740000

Absorption into the body leads to the formation of methemoglobin which in sufficient concentration causes cyanosis. Onset may be delayed 2 to 4 hours or longer. Vomiting, Diarrhea, Nausea, Dizziness, Headache.

Stomach - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION

Ecotoxicological information on this product or its components appear in this section when such data is available.

13. DISPOSAL CONSIDERATIONS

Environmental precautions: Prevent the material from entering drains or water courses. Advise Authorities if spillage has entered watercourse or sewer or has contaminated soil or vegetation.

Disposal

Dispose in accordance with all local, state (provincial), and federal regulations. Under RCRA, it is the responsibility of the product's user to determine at the time of disposal, whether the product meets RCRA criteria for hazardous waste. This is

because the product uses, transformations, mixtures, processes, etc. may render the resulting materials hazardous.

Do not remove label until container is thoroughly cleaned. Empty containers may contain hazardous residues. This material and its container must be disposed of in a safe way.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

IMO/ IMDG/ IATA

Not regulated (Not dangerous for transport)

Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations.

15. REGULATORY INFORMATION

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA TITLE III: Section 311/312 Categorizations (40CFR370): Immediate health hazard, Acute Health Hazard, Chronic Health Hazard

SARA TITLE III: Section 313 Information (40CFR372)

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

US. Toxic Substances Control Act (TSCA) All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

California (Proposition 65)

This product does not contain materials which the State of California has found to cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H372 Causes damage to organs through prolonged or repeated exposure.

H302 Harmful if swallowed.

STOT RE Specific target organ toxicity – repeated exposure

GENERAL ENGINEERING AND RESEARCH

Hazard Rating

| | Health | Chronic Health Hazard | Fire | Reactivity |
|-------------|--------|-----------------------------|------|------------|
| HMIS Rating | 1 | * | 0 | 0 |
| NFPA Rating | 0 | | 0 | 0 |

Legend

| ACGIH | American Conference of Governmental Industrial Hygienists |
|-------|---|
| OSHA | Occupational Safety and Health Administration |
| PEL | Permissible Exposure Limit |
| STEL | Short Term Exposure Limit |
| TLV | Threshold Limit Value |
| TWA | Time Weighted Average |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transporation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.