

Poly Stormer

Keep air moving efficiently across your animals or in commercial and industrial applications with J&D's Poly Stormer. Made with high CFM in mind, this economical fan will give you the efficiency you want and the air flow you deserve.

NEW!

Features

- Available in 36" single phase or three phase options
- Fan ships fully assembled
- Includes hot dip galvanized mounting bracket for versatile mounting options
- Quiet operation
- Direct Drive motor with no belts or bearings to maintain
- Totally enclosed, maintenance-free, high-efficiency motors have completely sealed ball bearings, UL and CUL recognized, and are covered by a **Two-Year Warranty**
- Polyethylene housing will not rust or corrode
- Galvanized G90 prop
- Guards are white powder coated for easy cleaning and corrosion resistance
- Stainless Steel fasteners
- Light weight for easy transporting
- Single phase model has automatic overload protection
- Can be used with our misting/fogging product line
- Assembled in America



Part#	Size	HP	Volts	Amps ^{NP}	Hz ^v	Spd	FPM	Thrust (lbf)	Thrust Eff. Ratio	kW	RPM	Thrust CFM	Thrust CFM/Watt	Drive	Prop	Test #
Single Phase																
VPS36A	36"	1/2	115/230	5.2/2.6	60	1	840	5.88	10.8	.543	849	8,070	14.9	Direct	3-Glv	C17002
Three Phase																
VPS36CF	36"	1/2	230/460	2.2/1.1	60	1	750	6.12	13.9	.440	853	8,240	18.7	Direct	3-Glv	C17006

All units include the corresponding hot dip galvanized standard flag mount bracket with hardware

^{NP} Amp information as documented on motor name plate

^v For 50 Hz compatibility data please contact J&D Manufacturing

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12

OSHA requires this fan to be mounted 7' above the floor

Due to our continual effort to provide the best products available and adhere to market conditions; literature, products, prices and availability are subject to change without notice.