

## Mega Storm 72" Fiberglass Exhaust Fan



### Features

- Certified performances up to 41,029 CFM @.10" SP
- Single or three phase **3 HP, UL recognized motors**
- Four-point contact X-frame for strength and durability
- UV resistant smooth molded fiberglass housing
- Twin Gates® size "A" belts are easily accessible and require no tools for replacement in seconds
- Double groove steel belt tensioner for longer life
- Quiet and smooth operation
- 5 bladed aluminum propeller
- Aluminum or poly shutters
- Available with or without one-piece molded cone
- Heavy gauge stainless steel shutter clips
- 1 ½" shaft and sealed pillow block bearings
- Heavy duty guard is hot dip galvanized after welding
- Bottom motor location for easy access when installed
- Drainage holes in the bottom of the housing for moisture
- **2 Year Warranty** on motors
- **3 Year Warranty** on bearings
- **10 Year Warranty** on propeller
- **20 Year Warranty** on fiberglass housing



Shown with Fiberglass Cone

Shown without Cone

**⚠ WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product).

*Due to our continual effort to provide the best products available and adhere to market conditions; literature, products, prices and availability are subject to change without notice.*

# Mega Storm

## 72" Fiberglass Exhaust Fan



Stainless steel heavy gauge shutter clips swivel by hand for easy removal of the shutter when it's time to clean or maintain your fan.



Twin Gates® size "A" belts are easily accessible and require no tools for replacement in seconds.

Part #	Size	Ph	Spd	@ 0.10" SP		Drive	Prop
				CFM	CFM/ Watt		
<b>Single Phase</b>							
<b>No Cone</b>							
<b>Aluminum Shutter</b>							
VMSA72A5N31	72"	1	1	39,364	11.9	Belt	5-Alm
<b>Poly Shutter</b>							
V MSP72A5N31	72"	1	1	39,364	11.9	Belt	5-Alm
<b>With Cone</b>							
<b>Aluminum Shutter</b>							
VMSA72A5C31	72"	1	1	<b>41,029</b>	<b>14.3</b>	Belt	5-Alm
<b>Poly Shutter</b>							
V MSP72A5C31	72"	1	1	<b>39,560</b>	<b>14.1</b>	Belt	5-Alm
<b>Three Phase</b>							
<b>No Cone</b>							
<b>Aluminum Shutter</b>							
VMSA72A5N33	72"	3	1	39,364	11.9	Belt	5-Alm
<b>Poly Shutter</b>							
V MSP72A5N33	72"	3	1	39,364	11.9	Belt	5-Alm
<b>With Cone</b>							
<b>Aluminum Shutter</b>							
VMSA72A5C33	72"	3	1	42,973	13.8	Belt	5-Alm
<b>Poly Shutter</b>							
V MSP72A5C33	72"	3	1	42,973	13.8	Belt	5-Alm

**Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 210-07**

Rough Opening  
77" W x 77" H  
Side-By-Side Recommended OC  
Dimension for Fan with Cone  
Minimum 81"



Heavy duty guard is hot dip galvanized after welding to protect from corrosion.

**⚠ WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product).  
 Due to our continual effort to provide the best products available and adhere to market conditions; literature, products, prices and availability are subject to change without notice.