

Portable Air Conditioner

Submittal Data

STANDARD FEATURES

- 21,000 BTU/Hr
- Compressor Time Delay
- Compressor Overload Protection
- High Pressure Switch
- Thermostat
- Anti-Freeze Thermostat
- Self-Diagnostic Function
- Automatic Restart



SPECIFICATIONS

Specification	Unit	6KK21
Cooling capacity	BTU/H	21,000
Power supply	Phase	Single phase
	Volt	230V
	Hertz	60
Size (W X D X H)	In	20.6 x 26.4 x 41.0
Weight	Lbs.	194
Current consumption	Amps	11
Power consumption	Kw	2.4
Air flow (Evaporator)	CFM	465 / 560
Air flow (Condenser)	CFM	1,190 / 1,380
Air filter (Condenser / Evaporator)		Aluminum / Vinylchloride
Refrigerant	Type	R-410A
Operating condition	°F	64.4-113
Hot air duct diameter	In	12
Condensate tank	Gal	4.75
Cooling area	Sq. Ft	538



260 North Elm St.
 Westfield, MA 01085
Phone: 413-564-5520
Fax: 413-564-5815
 www.Koldwave.com

Project: _____ Date: _____
 Location: _____
 Customer: _____
 Engineer: _____
 Submitted By: _____
 For: Reference Approval Construction
 Unit Designation: _____
 Schedule Number: _____