



## SPECIFICATIONS

Product Description: **8" (20.3 cm) AXIAL AC PLASTIC BLOWER**  
 Part Number: **9533, 9533-15, 9533-25, 9533-50**  
 Style: **WITH OR WITHOUT CANISTER & DUCTING**

### GENERAL DESCRIPTION:

High output from a compact axial blower, designed for easy use and storage without sacrificing airflow. Available as blower only or complete unit with 15' (4.75 m), 25' (7.62 m) or 50' (15.2 m) of ducting and storage canister. Canister attaches to intake or output of blower for suction or ventilation. Certified to CSA Standard C22.2 No.113.

### CONSTRUCTION:

- New compact canister in 9533-15 and 9533-25 models is the lightest and smallest in the industry!
- Polyethylene housing and canister assembly
- Lightweight, corrosion-, UV- and chemical-resistant
- Super quiet, in "safety orange"
- Bottom enclosure to protect electrical components
- Carry handle molded into blower and canister housing
- Steel powder coated grill

### MOTOR:

HP: 1/3 HP  
 Certification: UL Recognized, CSA Certified, CE Certified  
 Voltage/Hz: 115V-230V AC, 50/60 Hz, Single Phase  
 RPM: 2800/3400  
 Switch: ON/OFF Rocker  
 Amps: 4.8A-2.4A (50 Hz) / 4.5A-2.2A (60 Hz)  
 Cord: 10' (3.05 m) AWG  
 Plug: NEMA 5-15P

### FAN:

- Polypropylene nine blade fan

### DUCTING: (included on 9533-15, 9533-25 and 9533-50 models)

- Retractable, non-collapsible design
- Single-ply, PVC coated vinyl and polyester materials, temperature resistant up to 180° F (82.2° C)
- Yellow color with black weather strip and integrated nylon attachment strap
- Class 1 hard drawn spring steel wire helix that meets ASTM 227 specs

### BLOWER DIMENSIONS:

Blower PN	Length	Width	Height	Weight
9533	13 ¼" (33.6 cm)	12" (30.4 cm)	13 ¾" (34.9 cm)	17 lbs. (7.7 kg)
9533-15	26" (66.0 cm)	13 ½" (34.2 cm)	14 ½" (36.8 cm)	25 lbs. (11.3 kg)
9533-25	26" (66.0 cm)	13 ½" (34.2 cm)	14 ½" (36.8 cm)	30 lbs. (13.6 kg)
9533-50	32" (81.3 cm)	13 ½" (34.2 cm)	14 ½" (36.8 cm)	40 lbs. (18.1 kg)

### FLOW RATES: (CFM calculated using 15' (4.57 m) of 8" (20.3 cm) ducting)

Free Air	One 90° Bend	Two 90° Bends
831 CFM (1411.87 m <sup>3</sup> /hr)	709 CFM (1204.59 m <sup>3</sup> /hr)	586 CFM (995.62 m <sup>3</sup> /hr)



9533 (Blower only) , 9533-15, 9533-25



9533-50