



SPECIFICATIONS

Product Description: **12" (30.4 cm) AIR BAG BLOWER SYSTEM**
 Part Number: **9535-12, 9535-12L**
 Style: **AXIAL FAN**

GENERAL DESCRIPTION:

12" (30.4 cm) blower system with ducting built into a heavy duty bag. Zippered ends allow blower use without removing unit from bag. Combination Axial 12" (30.4 cm) blower, 15' (4.75 m) or 25' (7.62 m) duct and custom storage bag to house system. Certified to CSA Standard C22.2, No 113.



CONSTRUCTION:

- Lightweight, metal 12" (30.4 cm) blower
- Super quiet
- Carry handle with molded-in 2-speed switch
- Steel/powder coated housing and grills
- Unique bag with openings for plug/cord, inlet and outlet
- Durable reinforced polyester bag
- Easy to carry and store
- All-in-one unit for ease of operation
- Duct mounted on the blower and stored inside bag
- Both carrying handle and shoulder strap allow for easy transportation

MOTOR:

HP: 1/2 HP
 Certifications: UL Recognized, CSA Certified
 Voltage/Hz 120V AC, 60 Hz, Single Phase
 Amps: 3.8A
 Max RPM: 3300 (Loaded at 120 Volts, 60 Hz)
 Cord: 6' (1.82m) AWG
 Switch: 2-Speed on/off switch
 Plug: NEMA 5-15P 125V

FAN:

- Polypropylene seven blade fan

DUCTING:

- Single-Ply lightweight vinyl/polyester, PVC coated 180° F (82.2° C) temperature resistant
- Non-collapsible retractable design
- Yellow with black wear-strip and integrated nylon attachment strap on each end

DIMENSIONS:

Length	Width	Height	Weight
28" (71.1 cm)	16" (40.6 cm)	14" (35.5 cm)	35 lbs. (15.8 kg)

FLOW RATES: (free air calculated at blower)

1840 CFM (3126.2 m³/hr)

AVAILABLE:

9535-12DC 12" (30.4 cm) DC blower system with 15' (4.57 m) ducting
9535-12LDC 12" (30.4 cm) DC blower system with 25' (7.62 m) ducting