



SPECIFICATIONS

Product Description: **16" (40.6cm) PLASTIC COM-PAX-IAL BLOWER AC**
 Part Number: **9553, 9553-15, 9553-25**
 Style: **AXIAL FAN 16" (40.6cm) WITH OR WITHOUT CANISTER**

GENERAL DESCRIPTION:

Lightweight, portable and durable, this high output blower is ideally suited for large confined spaces such as paper mills, tank purging or utility sites. The quick-connect clipping system allows workers to attach the canister, tools free, to the input side for powerful extraction or output side for ventilation. Certified to CSA Standard C22.2 No.113.



CONSTRUCTION:

- Polyethylene "safety orange" color housing
- Lightweight, corrosion-, UV- and chemical-resistant
- Super quiet
- Carry handle molded into blower and canister housing
- Black plastic grill
- Built-in on/off switch and enclosed electrical components

MOTOR:

HP: 1 HP
 Certification: UL Listed, CSA Certified
 Voltage/Hz: 115V/60Hz, Single Phase
 RPM: 3450
 Amps: 9A
 Switch: Built in ON/OFF Rocker
 Cord: 20' (6.1m) (UL) SJT, 14 AWG
 Plug: NEMA 5-15P

FAN:

- Polypropylene three blade fan

DUCTING: *(included on 9553-15 and 9553-25 models)*

- Retractable, non-collapsible design, Single-ply
- PVC coated vinyl and polyester materials
- Yellow color with black weather strip and integrated nylon attachment strap
- Spring steel wire helix

BLOWER DIMENSIONS:

Blower P/N	Length In. (cm)	Width In. (cm)	Height In. (cm)	Weight Lbs. (Kg)
9553	20" (50.8 cm)	22.5" (57.1 cm)	22.5" (57.1 cm)	40 lbs (18.1 kg)
9553-15	34" (86.4 cm)	22.5" (57.1 cm)	22.5" (57.1 cm)	66 lbs (29.9 kg)
9553-25	34" (86.4 cm)	22.5" (57.1 cm)	22.5" (57.1 cm)	73 lbs (33.1 kg)

FLOW RATES: *(CFM calculated using 15' (4.57m) of 12" (30.4cm) ducting)*

Free Air CFM (m ³ /hr)	One 90° Bend CFM (m ³ /hr)	Two 90° Bends CFM (m ³ /hr)
3200 (5436.83)	2350 (3992.67)	2250 (3822.77)