



1826 Trade St. Florence, SC 29501

POB 5536 Florence, SC 29502

Phone: 843-667-9055

800-394-9739

Fax: 843-665-5006

Air Max High Velocity Fan Model AM-22

- AM22 have a four paddle, 22-inch diameter aluminum blade.
- The motor and blade are mounted in a 16 ga. steel venturi/housing that is 28.675 inches in diameter at the widest point. Inlet to outlet dimension is 18 inches.
- Guards are 3/8 inch spaced concentric steel wire guards that meet OSHA requirements are standard.
- Motors are TEAO, thermal protected. Standard units are ½ hp, single phase, 1725 rpm, 115v (6amps), 208v (2.9amps), 230v (3amps), or 277(2 amps). ½ hp, 3 phase, 1725 rpm, 208v (2.1amps), 230v (2.2amps), 460v (1.1amps).
Options are 1 hp, single phase, 115v (9.2amps), 230v (4.6amps). 1 hp, 3 phase, 208v (3.8 amps), 230v (3.6amps), 460v (1.9amps). 2hp, single phase, 115v, (18.8 amps), 230v, (9.4 amps). 2 hp, 3 phase 230v (5.8 amps), 460v (2.9 amps).
- All fan products are powder coated.
- All hardware is zinc coated grade 5 or better, nuts are nylon lock nuts.
- The ½- hp unit is rated at approximately 6,600 CFM; the 1-hp unit is rated at approximately 8,000 CFM, 2-hp unit is rated at approximately 12,000 CFM.
- Approximate shipping weight with 1/2 hp motor is 73 lbs., 1 hp motor is 85 lbs., 2hp motor is 102 lbs.
- 3 year limited warranty on material and workmanship. Fan motors are warranted by manufacturer warranty.
- Mount options: There are 9 options for mounting of this fan. GP, goal post (yoke) mount, WM, wall mount, CHM, chain suspension, CM, ceiling mount, TB, truck bay mount, PM, pole mount, ST, stroller mount, PST, pedestal stroller, HDPST, heavy duty pedestal stroller mount. Ask for mount overview with detailed information on each mount.

