



SPECIFICATIONS

Product Description: **8" (20.3cm) PLASTIC BLOWER**
 Part Number: **9539-08**
 Style: **AXIAL FAN 8" (20.3cm)**

GENERAL DESCRIPTION:

This portable blower is ideally suited for light industrial or utility application. This compact blower delivers maximum airflow and is perfect for confined spaces such as manholes. Certified to CSA Standard C22.2 No.113.

CONSTRUCTION:

- Lightweight-, corrosion-, UV-, and chemical-resistant polyethylene housing
- Durable construction design
- Super quiet
- "Safety orange"
- Bottom enclosure to protect electrical components
- Carry handle molded into blower



MOTOR:

HP: 1/3 HP
 Certifications: UL Recognized, CSA Certified
 Voltage/Hz: 115V AC, 60Hz, Single Phase
 Max RPM: 3400
 Switch: ON/OFF switch
 Amps: 4.8A-2.4A (50Hz) / 4.5A-2.2A (60Hz)
 Cord: 20' (6.09m) AWG
 Plug: NEMA 5-15P

DUCTING: *(Optional)*

- Retractable, non-collapsible design
- Single-ply, PVC coated vinyl and polyester materials. temperature resistant up to 180°F (82.2°C)
- Yellow color with black weather strip and integrated nylon attachment strap
- Class 1 hard drawn spring steel wire helix that meets ASTM 227 specs

BLOWER DIMENSIONS:

Length In (cm)	Width In (cm)	Height In (cm)	Weight Lb (Kg)
15" (38.1)	12½" (31.7)	18½" (46.9)	16 (7.2)

FLOW RATES: *(CFM calculated using 15' (4.57m) of 8" (20.3cm) ducting)*

Free Air CFM (m³/hr)	One 90° Bend CFM (m³/hr)	Two 90° Bends CFM (m³/hr)
865 (1469.64)	550 (934.45)	350 (594.65)