

EPET Series and HLT Series Hazardous Location



- Motor Rating (full load): 3/4 HP @ 125V,
1-1/2 HP @ 250V
- Pilot Duty Rating 125VA @ 24VAC
- NEMA Class Seven Div. 1 Approved
- Class I Group C & D, Class II Group E, F, & G
- Not rated for Group B

WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

Features

- SPDT & DPDT Models
- Heat or cool compatible
- Celsius and Fahrenheit temperature scale
- Bi-Metal or capillary sensor
- Snap action switch
- Casting tapped top and bottom for 3/4" conduit
- 1/2" thick cast aluminum housing
- All EPET optional thermostats manufactured with anti-static plastic
- Dimension 5.75" x 6.375" x 5.57"
- Made in U.S.A.

MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION	LOAD RATINGS	RANGE	LIST
05380702	EPETD8D	DPDT - Bi-Metal	22A @120-277VAC	50-90°F	438
05381002	EPETD8S	SPDT - Bi-Metal	22A @120-277VAC	50-90°F	438
05280702	EPETP8D	DPDT - Bi-Metal	22A @120-480VAC	50-90°F	438
05280602	EPETP8S	SPDT - Bi-Metal	22A @120-480VAC	50-90°F	438
05231502	HLT-1	SPDT - Capillary	22A @120-277VAC	40-110°F	601
05231602	HLT-2	DPDT - Capillary	22A @120-277VAC	40-110°F	635
Master ctn: 4 pcs, 24 lbs (varies slightly by model), 16" x 14.5" x 6"					
EPET Series incorporate plastic knob & Bi-Metal Sensor housing					
HLT Series incorporates screwdriver temperature adjustment slot and all metal housing. External bulb and capillary sensor.					