

TPI Industrial Mini-Blowers



FLOOR MODEL



YOKE MOUNTED MODEL



WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.



MBM-W
(Optional Wall/
Ceiling Mount)

TOTALLY ENCLOSED MOTOR ALLOWS MINI-BLOWER TO BE USED IN DIRTY OR DUSTY ENVIRONMENTS.

AVAILABLE AS FLOOR MODEL OR YOKE MOUNTED MODEL THAT CAN BE DIRECTLY BOLTED TO ANY SURFACE OR USED WITH OPTIONAL WALL/CEILING MOUNT.

Features

- Floor models have rotary switch
- Yoke mounted models have pull chain switch
- SJT type 3 conductor, 10' long cord
- Aluminum blade
- Spiral, wire front and rear guards
- Corrosion and dent proof high density polyethylene housing
- Meets OSHA standards
- 1 year limited warranty
- Made in U.S.A. with domestic and foreign components

Motor Specifications

- 1-Phase
- 1/4 HP
- Ball bearing
- Totally enclosed
- 120V
- 2-Speed
- Permanently lubricated
- Permanent split capacitor

Standard Models

MFG CATALOG NUMBER	MFG MODEL NUMBER	FAN		CFM* / RPM		VELOCITY PROFILE CFM / Area Sq Ft	DIMENSIONS			AMPS (High)	WT. (LBS)
		TYPE	SIZE	HIGH	LOW		"H"	"W"	"D"		
08743502	MB 24-DF	FLOOR STYLE	24"	3300 / 1140	2900 / 1070	5200 / 240	29 1/2"	28 1/2"	14 1/4"	2.2	52
08743602	MB 24-DY	YOKE STYLE		4400 / 1040	3900 / 730		7000 / 250	38 1/2"	37 1/2"		
08743702	MB 30-DF	FLOOR STYLE	30"	4400 / 1040	3900 / 730	7000 / 250	38 1/2"	37 1/2"	14 1/2"	2.5	58
08743802	MB 30-DY	YOKE STYLE									
07989002	MBM-W	OPTIONAL WALL/CEILING MOUNT FOR YOKE STYLE MINI-BLOWER									4

*Measured 2 feet from face of fan

TPI Industrial High Velocity Blowers

**NEW PRODUCT
for 2020**



WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

Features

- Aluminum blade
- Spiral, wire front and rear guards
- Wall and ceiling mounting options
- Gray epoxy powdercoated housing
- 2 year limited warranty
- Made in U.S.A.
- Stationary
- Direct drive

Motor Specifications

- 1-Phase
- Ball bearing motor
- 1/2 or 1 HP
- TEAO
- Single speed
- 373 & 746 watts
- Automatic thermal protection

MOUNTING BRACKETS

MFG CATALOG NUMBER	MFG MODEL NUMBER	SIZE	WT. (LBS)
08197502	HV-1	18"	14
08197602	HV-2	24"	22
08197702	HV-3	30"	24

Standard Models

SIZE	MFG CATALOG NUMBER	MFG MODEL NUMBER	VOLTS	PHASE	HP	WATTS	CFM / RPM	DIMENSIONS			AMPS (High)	WT. (LBS)
								"H"	"W"	"D"		
18"	HV18-120V	08195602	120	1	1/2	373	3000 / 1725	25.12"	23.63"	13.5"	5.0	45
	HV18-208/240V	08195702	208/240								2.6	
	HV18-277V	08195802	277								2.1	
	HV18-480V	08195902	480								1.3	
	HV18-480V-3	08197202	480								1.0*	
24"	HV24-120V	08196002	120	1	1/2	373	5290 / 1725	30.5"	29.63"	13.5"	5.0	58
	HV24-208/240V	08196102	208/240								2.6	
	HV24-277V	08196202	277								2.1	
	HV24-480V	08196302	480								1.3	
	HV24-480V-3	08197302	480								1.0*	
30"	HV30-120V	08196402	120	1	1	746	9000 / 1700	38"	34.63"	16"	10.0	85
	HV30-208/240V	08196502	208/240								4.7	
	HV30-277V	08196602	277								3.6	
	HV30-480V	08196702	480								2.1	
	HV30-480V-3	08197402	480								1.7*	

*Values listed are estimates at time of printing