



KWIB12043

LEGEND

- | | |
|--------------------------|-------------------------|
| 1 Cold Air Return | 6 Cord Storage |
| 2 Control Pad | 7 Condensate Nipple |
| 3 Cold Air Supply | 8 Condensate Alarm Jack |
| 4 Condenser Water Inlet | 9 Access Door |
| 5 Condenser Water Outlet | 10 Vent Control |



ETL LISTED CONFORMS TO ANSI/UL1995
CERTIFIED TO CAN/CSA 22.2 NO 235

1-800-KWIKOOL

www.kwikool.com



SPECIFICATIONS

KWIB12043

COOLING CAPACITY	BTU/hr @ 95F at 60% RH	120,000 (10-Ton)
COMPRESSOR DATA	Compressor Type	Hermetic Recip. (2 stage)
	Operating Temperatures	60-110 F 50%RH
	Refrigerant	407C
FAN DATA Evaporator	Fan Type (Centrifugal)	Direct Drive
	Air Flow (CFM)	1800/3800
	Supply Air Device	Adjustable Vent
	Supply Air Chute Kit (optional)	2 - 12" Dia. x 30" Length
Condenser Water Flow Data	Flow Regulating Valve 1/2"NPT	Automatic
	Inlet Water 85F-95F Exit (GPM)	30
	Inlet Water 75F-95F Exit (GPM)	15
	Inlet Water 65F-95F Exit (GPM)	10
	Inlet Water 55F-95F Exit (GPM)	7.5
	Cooling Loops (2)	Dual inlets and outlets
ELECTRICAL DATA	Power Supply (Volts)	460 Three Phase
	Current Consumption (Amps)	19.4
	Power Consumption (kW)	13.9
	Maximum Circuit Breaker (Amps)	30
	Recommended Breaker Size	30
	Minimum Circuit Ampacity (Amps)	25.7
	Min./Max. Voltage	420-500
	Power Cord Gauge/Length	10AWG/10'
	Plug Configuration	Field Supplied
DIMENSIONAL DATA	Width x Depth x Height (Inches)	32.325" x 36.5" x68.25"
	Weight (Lbs.)	766
	Shipping Weight (Lbs.)	826
SAFETY DEVICE DATA	Compressor Overload	Internal
	Fan Motor Overload	Automatic Internal
	Evaporator Freeze Protection	Hot Gas Bypass
	High Pressure Switch	Manual
	Low Pressure Switch	Automatic
	Compressor Short Cycle	Yes
	Automatic Restart	Yes
	Thermostat Type	Microprocessor/Digital
	Condensate Pump Overflow	Yes
	Condensate Tank Overflow	Yes

1-800-KWIKOOL

www.kwikool.com