



# LF - HIGH VELOCITY CEILING OR WALL FAN

Suitable for wet locations.

## FEATURES

- Ceiling or wall mount high velocity fan.
- 18" blade diameter.
- Commercial duty 3 speed motor with pull chain control.
- All metal construction.
- 1/8 hp motor.
- Epoxy coated OSHA guard.
- 9' heavy duty 120V cord with cord wrap.
- Steel wall (ceiling) mount assembly.

## PERFORMANCE SPECIFICATIONS

MODEL	SIZE	H.P.	VOLTS	AMPS	Phs	RPM	SPEED	CFM	WEIGHT (LBS)
LF18HWV	18"	1/8	120	1.45/1.35/1.27	1	1290/960/760	3	5700/4100/3200	26



HAF18

# HAF - HORIZONTAL AIR FLOW FANS

Suitable for wet locations.

The HAF18 features a 1/6 HP totally enclosed, 115V, 0.9 amps motor. The variable speed motor can be adjusted accordingly to meet your requirements. It features open guard spacing for better air distribution and a hanging bracket. When suspended, fan can pivot up and down and swivel 360° for optimal control of air stream.

## FEATURES

- 18" horizontal air flow fan
- Totally enclosed motor
- Powder coated guard has wide spacing to eliminate the build up of debris.
- Suitable for wet locations
- 115V, 8 foot grounded cord & plug
- Zinc dipped OSHA guard option available

## PERFORMANCE SPECIFICATIONS

MODEL	BLADE DIAMETER	MOTOR SIZE (HP)	PHS	VOLTS	AMPS	MOTOR RPM	SPEED	CFM	SHIPPING WEIGHT (LBS.)
HAF18	18"	1/6	1	115	0.9	1,400	Variable	4,000	22
HAF18-ZO	18"	1/6	1	115	0.9	1,400	Variable	4,000	22



HAF18-ZO