

# THE PORTABLE COOLER"

For years, the Portable Cooler, (cousin to our Heat Buster, but in the more economical direct-drive) has been the worldwide choice of many for portable spot-cooling in factories, workshops, dairies, livestock barns, aircraft hangars, homes, patios, etc.

#### **Features:**

- Direct Drive
- Heavy guage steel barrels
- Deep pitched blades for maximum air flow
- Osha Approved Spiral Wound Guard
- 115 volt, 60 hertz, single phase, one or two speed motors







#### PORTABLE COOLER HD

- Tough, Rugged and Durable
- Deep pitched blades
- Switch Guard

The Portable Cooler HD is one of the most rugged and dependably built, direct drive fans on the market and is engineered to provide long lasting spot cooling for people, products and equipment.

Model	Blade Diameter	CFM	RPM	HP	Amps	Width	Depth	Height	Approximate Weight
PC3613	36"	10,900	825	1/2	6.0	39"	21"	40"	111
PC3623	36"	10,900 / 8,800	825 / 680	1/2	6.0	39"	21"	40"	111
PC4213	42"	13,600	825	1/2	6.0	45"	21"	46"	121
PC4223	42"	13,600 / 10,500	825 / 680	1/2	6.0	45"	21"	46"	121
PC4815	48"	19,100	850	1	9.1	51"	25"	52"	193



#### THE PORTABLE COOLER

- Economical Cooling
- Durable steel barrel
- Two Speed

The Portable Cooler is our most economical direct drive portable barrel fan. It offers superb airflow in a rugged and easy to move design.

Model	Blade Diameter	CFM	RPM	HP	Amps	Width	Depth	Height	Approximate Weight
QBD 3623	36"	10,900 / 8,800	830 / 770	1/2	6.1	39"	21"	39"	96
QBD 4223	42"	13,200 / 10,200	770 / 660	1/2	6.1	45"	21"	45"	101



## The HBPC

- Tough, Rugged and Durable
- Full Width Easy Grip Handle
- Tilts up or down with positive tilt lock knob

The "HBPC" employees the same great design of the Portable Cooler HD while adding a cradle mount, allowing for precise, directional cooling of people, products or equipment.

Model	Blade Diameter	CFM	RPM	HP	Amps	Width	Depth	Height	Approximate Weight
HBPC 3613	36"	10,900	825	1/2	6.0	45"	27"	50"	192
HBPC 3623	36"	10,900 / 8,800	825 / 680	1/2	6.0	45"	27"	50"	192
HBPC 4213	42"	13,600	825	1/2	6.0	51"	27"	54"	202
HBPC 4213 W*	42"	13,600	825	1/2	3.0	51"	27"	54"	202
HBPC 4223	42"	13,600 / 10,500	825 / 680	1/2	6.0	51"	27"	54"	202
HBPC 4815	48"	19,100	850	1	9.1	58"	27"	60"	228
HBPC 4815 W*	48"	19,100	850	1	4.5	58"	27"	60"	228

<sup>\*230</sup> VOLT SINGLE PHASE MOTORS



### **PORTABLE COOLER MINI**

- Deep pitched blades
- Spiral wound wire guard
- 115 volt 60hz, two speed motor
- Caddy cart handle for easy manuverability

The Portable Cooler Mini has all of the great design of the Portable Cooler HD but in a slim, light weight design, making it ideal for work shops, garages and sporting events.

Model	Blade Diameter	CFM	RPM	ΗP	Amps	Width	Depth	Height	Approximate Weight
PC3021	30"	8,200 / 6,600	1,090 / 1,010	1/4	3.5	33"	15"	34"	55



#### **CONTRACTOR'S FAN**

- Tilt up or down 90 degrees
- 115 volt, 60hz, two speed motor
- Spiral wound wire guard

Triangle's Contractor Fan is great for home use, farm use, work shops, garages, sporting events, and camp sites.

Model	Blade Diameter	CFM	RPM	HP	Amps	Width	Depth	Height	Approximate Weight
CF 2421	24"	3,800 / 6,600	1,100 / 950	1/4	3.5	29"	16"	31"	48