



	1		
Motor Voltage	120 VAC, 60 Hz		
Energy Use	Hi: 769 Watts / Low: 560 Watts		
Air Flow	Hi: 5665 CFM / Low: 4289 CFM		
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers up to 2840 SQ FT		
# of Speeds	2		
Duct Diameter	22"		
Duct Length	9 feet		
Motor Head Diameter	22 1/2"		
Motor Head Length	13 1/2"		
Dampers	Barometric Pressurized R5 Dampers		
Controls (Not Included)	Recommended 8 Hour Electronic 1	ectronic Timer (IT-30070) and	
	HI-LOW-OFF Switch (IT-35000)		
Warranty	10 Years		
Framing	None Required		
Joist Cutting	None Required; fits 16" or 24" on center		
Minimum Suggested Attic Venting	7.56 SQ FT net free area		
Ceiling Rough Opening	14 1/4" x 36 1/4"		
Removable Grille Outside Dimension	16" x 38"		
Shipping Weight	103 lbs.		
Box Dimensions	41" x 26" x 39"		
In The Box	-QC CL-6000 Motorhead	-Damper Box	
	-Ceiling Grille	-9 Foot Duct	
	-Cut-out Template	-Accessory Bag	
	-Window Locks		

