



QC CL-7000
QuietCool Original Classic Line

QC CL-7000 Specifications

| | | |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Motor Voltage | 120 VAC, 60 Hz | |
| Energy Use | Hi: 1147 Watts / Low: 794 Watts | |
| Air Flow | Hi: 6924 CFM / Low: 5518 CFM | |
| Recommended SQFT Coverage @ 2 CFM per SQ FT | Covers up to 3470 SQ FT | |
| # of Speeds | 2 | |
| Duct Diameter | 24" | |
| Duct Length | 9 feet | |
| Motor Head Diameter | 24 1/2" | |
| Motor Head Length | 13 1/2" | |
| Dampers | Barometric Pressurized R5 Dampers | |
| Controls (Not Included) | Recommended 8 Hour Electronic Timer (IT-30070) and HI-LOW-OFF Switch (IT-35000) | |
| Warranty | 10 Years | |
| Framing | None Required | |
| Joist Cutting | None Required; fits 16" or 24" on center | |
| Minimum Suggested Attic Venting | 9.24 SQ FT net free area | |
| Ceiling Rough Opening | 14 1/4" x 36 1/4" | |
| Removable Grille Outside Dimension | 16" x 38" | |
| Shipping Weight | 108 lbs. | |
| Box Dimensions | 41" x 28" x 39" | |
| In The Box | <ul style="list-style-type: none"> -QC CL-7000 Motorhead -Ceiling Grille -Cut-out Template -Window Locks | <ul style="list-style-type: none"> -Damper Box -9 Foot Duct -Accessory Bag |



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM