

Shuttered Galvanized Box Fans

Model	Prop Type	HP	RPM	Drive	Phase	Volts	Amps	CFM @ 0.0 SP	CFM @ 0.1 SP	CFM @ 0.2 SP	CFM @ 0.3 SP
24D370S	24" 3 wing	1/2	1100	Direct	1	115 / 208-230	5.6 / 3.0-2.8	5,140	4,350	3,720	3,170
36D370S	36" 3 wing	1/2	825	Direct	1	115 / 208-230	5.2 / 2.8-2.6	10,300	8,720	7,180	5,820
36D370TS	36" 3 wing	1/2	825	Direct	3	208-230 / 460	2.3-2.2 / 1.1	10,315	8,730	7,185	5,825
36D550S	36" 3 wing	3/4	1100	Direct	1	115 / 208-230		11,330	9,590	7,980	6,520
36XL550S	36" 4 wing	3/4	715	Belt	1	115 / 208-230	6.4 / 3.4-3.2	11,010	9,580	8,210	5,470
36XL750S	36" 4 wing	1		Belt	1	115 / 208-230	9.4 / 5.0-4.7				
36XL750TS	36" 4 wing	1		Belt	3	208-230 / 460	3.8-3.6 / 1.8				
42D750S	42" 3 wing	1	825	Direct	1	115 / 208-230	11.0 / 5.8-5.5	14,970	12,060	10,840	6,640
42D750TS	42" 3 wing	1	825	Direct	3	208-230 / 460	4.8-4.6 / 2.3	14,995	12,085	10,860	6,655
42XL750S	42" 5 wing	1	560	Belt	1	115 / 208-230	9.4 / 5.0-4.7	15,250	12,280	9,110	5,490
42XL750TS	42" 5 wing	1	560	Belt	3	208-230 / 460	3.8-3.6 / 1.8	15,265	12,295	9,125	5,500
42XL1125S	42" 5 wing	1 1/2		Belt	1	208-230					
42XL1125TS	42" 5 wing	1 1/2		Belt	3	208-230 / 460	5.0-4.8 / 2.4				
48XL750S	48" 3 wing	1	595	Belt	1	115 / 208-230	9.4 / 5.0-4.7	19,050	17,010	14,670	11,070
48XL750TS	48" 3 wing	1	595	Belt	3	208-230 / 460	3.8-3.6 / 1.8	19,070	17,030	14,685	11,080
48XL1125S	48" 4 wing	1 1/2		Belt	1	208-230		22,860	20,920	18,050	12,350
48XL1125TS	48" 4 wing	1 1/2		Belt	3	208-230 / 460	5.0-4.8 / 2.4	22,875	20,930	18,060	12,355

Dimensions

Model:	Dim	Dim	Dim	Dim
24D370S	27.5	27.5	16.25	14.25
36D370S, 36D370TS	40.13	40.13	16	14
36D550S	40.13	40.13	16	14
36XL550S	40.13	40.13	26	24
36XL750S, 36XL750TS	40.13	40.13	26	24
42D750S, 42D750TS	46.13	46.13	26	24
42XL750S, 42XL750TS	46.13	46.13	26	24
42XL1125S, 42XL1125TS	46.13	46.13	26	24
48XL750S, 48XL750TS	52.13	52.13	26	24
48XL1125S, 48XL1125TS	52.13	52.13	26	24

