

MODEL

G130



Maximum filter life will be achieved with this product when one welder is welding up to 10 pounds of weld wire per week



Capacity: 150 CFM Max, 110 in.W.G. Max

Motor: 2.3 HP (1700 Watts), Direct Drive, 1500+ hr. Duty

Voltage: Single phase, 110V, 60Hz

Full Load Amps: 15.1

Blower: Single Stage Tapered 8.4" dia. Tangential Discharge Blower

Sound Level: 75 dBA

Silencing: Integral Acoustical Plenum with Low Frequency Dampening

Controls: Manual on/off switch, Minihelic Filter Condition Gauge

Cabinet Dimensions (HxLxD): 18" x 16" x 14"

Weight: 50 lbs.

Filter Cartridge: (1) EX-10D12-A15

Filter Media Area: 37 sq.ft.

Filter Type: Nanofiber MERV15

Dust Containment: Vacuum / sweep out filter plenum

Spark Arrestance: (1) Metal Mesh Screen MM-12121

Configuration: (1) 2" Flex Hose, 15'

Filter Cleaning: Ball-Valve Activated Pulse Cleaning, 1/4" NPT Compressed Air Connection

Options:

- Weld Current Sensor & Timer Module — VB-CST-2
- Intake Attachment Options:
 - Flared Cone 7" H x 10" W — FC-VB (**included**)
 - Slotted Hood 15" L — ST-VB
 - 2" Pipe with magnetic base — GNT-VB
- CSA Certification — CSA-100
- UL Certification — Contact Customer Service

Warranty:

Visit ventboss.com/terms for full warranty details.

