Data Sheet

Comb Baffle Assembly





-

Specifications		Technical	
Application Surface	Ceiling	NRC Rating*	0.85
Material	Acoustic felt P.E.T. 12mm, ½ lb per sqft (±6%)	Fire Test*	ASTM E84: Class A
Standard Sizes	Length: 23", 31" or 47" Width: 23", 31" or 47" Height: 8¾"		Flame spread index: 10 Smoke developed index: 250
			CAN/ULC S102
			Flame spread classification: 15
Custom Sizes	Available, see the next page on how to specify.		Smoke developed classification: 210
		* Full reports sucilable upon request	

*: Full reports available upon request.

Environmen	tal	SOUND ABSORPTION REPORT Acoustical Baffles, felt (9 units in 4 rows spaced 30 in. on center)	20- 15- 10- 10-	\sum
Recycled Content	Minimum 60%			
Recyclability	100% at participating facilities		Smoke (%A)	Z
Details		0.1	2000- 1500- 1000- 500- 500- 20-	\sum
Standard Lead Time	3 weeks to ship		0	
Origin	Manufactured in Canada	_		
Warranty*	5 years limited	—		

*: See TheQuietRoom Care Guide & Warranty for details.



Standard Sizes		Specify C	Specify Custom Sizes	
Length	23", 31" or 47"	Max Length	107"	
Width	23", 31" or 47"	Max Width	107"	
Height	8¾"	Max Height	23 ³ ⁄4"	
Material Thickness	12mm/0.47" (±6%)	Material Thickness	Material Thickness is not customizable at this time	



Finish Options

For printed felt, see TheQuietRoom Print Options (separate document from this data sheet).



Installation

CEILING HARDWARE OPTIONS



Installation

