

# 03 Series

## Polyurethane Wheel With Double Ball Bearing



# 40-142kg



Press Riveting frame is 30% stronger than Spindle Riveting.



1. Horn: Double Ball raceways design, black colour painted
2. Wheel: Black Polyurethane (90A-95A)/ Blackthread guards (Central precision ball bearings)
3. Suggest to use for many field with different environment. Temperature range: -20 °c ---80°C



B03-02B-50-201



B03-04-75-201



B03-01-100-201



B03-01D-125-201



B03-03-100-201



B03-03D-125-201

Wheel Dia (mm)	Thread Width (mm)	Load Capacity (kg)	Wheel Material	Loading Height (mm)	Swivel Radius (mm)	Brake Swivel Radius (mm)	Plate Size (mm)	Thread Size (mm)	Hollow Size (mm)	NO. Model
50 (2")	26	40	Polyurethan	74	45		(A)55×35 (B)70×55 (C)49×35 (D)8.5	M10×25		B03-04-50-201
										B03-01-50-201
										B03-01D-50-201
										B03-02-50-201
										B03-02B-50-201
75 (3")	32	100	Polyurethan	105	73	100	(A)78×45 (B)95×66 (C)71×45 (D)8.5	M12×25		B03-04-75-201
										B03-01-75-201
										B03-01D-75-201
									Φ13	B03-02-75-201
										B03-02D-75-201
										B03-03-75-201
100 (4")	32	130	Polyurethan	130	87	100	(A)78×45 (B)95×66 (C)71×45 (D)8.5		Φ13	B03-04-100-201
										B03-01-100-201
										B03-01D-100-201
										B03-03-100-201
										B03-03D-100-201
125 (5")	32	142	Polyurethan	142	100	108	(A)78×45 (B)95×66 (C)71×45 (D)8.5		Φ13	B03-04-125-201
										B03-01-125-201
										B03-01D-125-201
										B03-03-125-201
										B03-03D-125-201