





# TECHNICAL DATA

## Alloy Grade 'S' Shackles

To AS 2741-2002

DEE SHACKLE WITH SCREW PIN	WORKING LOAD LIMIT METRIC TONNES	MATERIAL DIAMETER BOW d mm	MATERIAL DIAMETER PIN D mm	DEE INSIDE WIDTH W mm	BOW INSIDE WIDTH W mm	INSIDE LENGTH	
						DEE SHACKLE L mm	BOW SHACKLE L mm
	0.33	5.0	6.0	10.0	15	16.0	22.0
	0.5	6.0	8.0	12.0	20	22.0	29.0
	0.75	8.0	10.0	13.0	21	26.0	31.0
	1.0	10.0	11.0	17.0	26	32.0	37.0
	1.5	11.0	13.0	18.0	29	37.0	43.0
	2.0	13.0	16.0	21.0	33	41.0	48.0
	3.2	16.0	19.0	27.0	43	51.0	61.0
	4.7	19.0	22.0	32.0	51	60.0	72.0
	6.5	22.0	25.0	37.0	58	71.0	84.0
	8.5	25.0	29.0	43.0	68	81.0	95.0
	9.5	29.0	32.0	46.0	74	90.0	108.0
	12.0	32.0	35.0	52.0	83	100.0	119.0
	13.5	35.0	38.0	57.0	92	113.0	133.0
	17.0	38.0	41.0	60.0	98	124.0	146.0
	25.0	44.0	51.0	73.0	127	146.0	178.0
	35.0	51.0	57.0	83.0	146	171.0	197.0
	45.0	57.0	63.0	95.0	160	181.0	222.0
	55.0	63.0	70.0	105.0	184	203.0	267.0
	85.0	76.0	83.0	127.0	200	229.0	330.0
	120.0	89.0	95.0	146.0	241	267.0	381.0
	150.0	102.0	108.0	165.0	279	318.0	432.0



PH: (03) 9792 3949 FAX: (03) 9791 2484

sales@dandenongcastors.com.au

415 Hammond Rd, Dandenong VIC 3175