

S SERIES CASTORS

MAX LOAD RATING
500KG

FEATURES

- » Pressed metal frames
- » Zinc plate finish
- » Metal brake pedal
- » Feature patented Patriot (UPB) and Commander (TPB) wheels with Quad Plus bearing system
- » 100mm, 125mm, 150mm and 200mm wheel diameters
- » All non marking, choice of hard and soft treads


COMMON USES

- » Factory machinery
- » Heavy duty trolleys
- » Workshop benches
- » Waste bin skips
- » Airport ground service equipment
- » Removalists trolley



PLATE SIZE

- » 135mm x 110mm
- » Hole centres 105mm x 80/75 (11)



BPB

- » Resilient blue rubber tread
- » Polypropylene centre
- » Precision bearings



NNI

- » Virgin nylon 6 tread
- » Nylon centre
- » Delrin bushes, POM spacer



NNB

- » Virgin nylon 6 tread
- » Nylon centre
- » Precision bearings



TPB COMMANDER

- » Thermoplastic elastomer tread
- » Polypropylene centre
- » Quad plus precision bearing system



UPB PATRIOT

- » Polyurethane tread
- » Polypropylene centre
- » Quad Plus precision bearing system



UPRB

- » Red rounded profile polyurethane tread
- » Polypropylene centre
- » Precision bearing

WHEEL DIAMETER (mm)	MOUNTING TYPE	FRAME CODE	WHEEL ABR	MAX LOAD (KG)	WHEEL ABR	MAX LOAD (KG)	WHEEL ABR	MAX LOAD (KG)	WHEEL ABR	MAX LOAD (KG)	WHEEL ABR	MAX LOAD (KG)	WHEEL ABR	MAX LOAD (KG)	OVERALL HEIGHT (mm)	SWIVEL RADIUS (mm)
100	RIGID	SZR10050	-BPB	150	-NNI	350	-NNB	400	-TPB	250	-UPB	300	-	-	135	-
125		SZR12550	-BPB	200	-NNI	400	-NNB	450	-TPB	300	-UPB	400	-	-	160	-
150		SZR15050	-BPB	250	-NNI	450	-NNB	500	-TPB	350	-UPB	500	-UPRB	500	180	-
200		SZR20050	-BPB	300	-NNI	500	-NNB	500	-TPB	400	-UPB	500	-	-	235	-
100	SWIVEL	SZS10050	-BPB	150	-NNI	350	-NNB	400	-TPB	250	-UPB	300	-	-	135	110
125		SZS12550	-BPB	200	-NNI	400	-NNB	450	-TPB	300	-UPB	400	-	-	160	116
150		SZS15050	-BPB	250	-NNI	450	-NNB	500	-TPB	350	-UPB	500	-UPRB	500	180	126
200		SZS20050	-BPB	300	-NNI	500	-NNB	500	-TPB	400	-UPB	500	-	-	235	160
100	TOTAL LOCKING	SZST10050	-BPB	150	-NNI	350	-NNB	400	-TPB	250	-UPB	300	-	-	135	140
125		SZST12550	-BPB	200	-NNI	400	-NNB	450	-TPB	300	-UPB	400	-	-	160	140
150		SZST15050	-BPB	250	-NNI	450	-NNB	500	-TPB	350	-UPB	500	-UPRB	500	180	140
200		SZST20050	-BPB	300	-NNI	500	-NNB	500	-TPB	400	-UPB	500	-	-	235	160

WHEELS

WHEEL DIAMETER (mm)	TREAD WIDTH (mm)	WHEEL CODE	MAX LOAD (KG)	BORE DIAMETER (no spacer mm)	BORE DIAMETER (spacer mm)	HUB LENGTH (mm)	TREAD MATERIAL	CENTRE MATERIAL	BEARING TYPE	AXLE SPACER TYPE
100	50	BP10050B	150	17MM	1/2"	60	BLUE HIGH RES	POLYPROPYLENE	PRECISION BEARINGS	SLEEVE
125	50	BP12550B	200	17	1/2"	60				TOP HAT
150	50	BP15050B(20)	250	20	1/2"	60				
200	50	BP20050B(20)	300	20	1/2"	60				
100	50	NN10050I	350	19	1/2"	60	NYLON	NYLON	DELTRIN BUSHINGS	POM TUBE SPACER
125	50	NN12550I	400	19	1/2"	60				
150	50	NN15050I	450	19	1/2"	60				
200	50	NN20050I	500	19	1/2"	60				
100	50	NN10050B	400	20	1/2"	60	NYLON	NYLON	PRECISION BEARINGS	
125	50	NN12550B	450	20	1/2"	60				
150	50	NN15050B	550	20	1/2"	60				
200	50	NN20050B	550	20	1/2"	60				
100	50	TP10050B	250	12.7	-	60	THERMOPLASTIC ELASTOMER	POLYPROPYLENE	QUAD-PLUS PRECISION BEARINGS	-
125	50	TP12550B	300	12.7	-	60				-
150	50	TP15050B	350	12.7	-	60				-
200	50	TP20050B	400	12.7	-	60				-
100	50	UP10050B	350	1/2"	-	60	URETHANE	POLYPROPYLENE	QUAD-PLUS PRECISION BEARINGS	-
125	50	UP12550B	400	1/2"	-	60				-
150	50	UP15050B	500	1/2"	-	60				-
200	50	UP20050B	550	1/2"	-	60				-
150	50	UPR15050B	450	17	1/2"	60	ROUND PROFILE URETHANE	POLYPROPYLENE	PRECISION BEARINGS	TOP HATS