

Slings supplied in pail with your reseller information.



**Custom Slings  
made to order**

### FOUR LEG CHAIN SLINGS WITH SHORTENING GRAB HOOK & SELF LOCKING HOOK

CODE	CHAIN SIZE	EFFECTIVE LENGTH	W.L.L
CS6MM4L1.0M	6mm	1.0mtr	1900kg @ 60°
CS6MM4L2.0M	6mm	2.0mtr	1900kg @ 60°
CS6MM4L3.0M	6mm	3.0mtr	1900kg @ 60°
CS6MM4L4.0M	6mm	4.0mtr	1900kg @ 60°
CS6MM4L5.0M	6mm	5.0mtr	1900kg @ 60°
CS6MM4L6.0M	6mm	6.0mtr	1900kg @ 60°
CS7MM4L1.0M	7mm	1.0mtr	2600kg @ 60°
CS7MM4L2.0M	7mm	2.0mtr	2600kg @ 60°
CS7MM4L3.0M	7mm	3.0mtr	2600kg @ 60°
CS7MM4L4.0M	7mm	4.0mtr	2600kg @ 60°
CS7MM4L5.0M	7mm	5.0mtr	2600kg @ 60°
CS7MM4L6.0M	7mm	6.0mtr	2600kg @ 60°
CS8MM4L1.0M	8mm	1.0mtr	3500kg @ 60°
CS8MM4L2.0M	8mm	2.0mtr	3500kg @ 60°
CS8MM4L3.0M	8mm	3.0mtr	3500kg @ 60°
CS8MM4L4.0M	8mm	4.0mtr	3500kg @ 60°
CS8MM4L5.0M	8mm	5.0mtr	3500kg @ 60°
CS8MM4L6.0M	8mm	6.0mtr	3500kg @ 60°
CS10MM4L1.0M	10mm	1.0mtr	5500kg @ 60°
CS10MM4L2.0M	10mm	2.0mtr	5500kg @ 60°
CS10MM4L3.0M	10mm	3.0mtr	5500kg @ 60°
CS10MM4L4.0M	10mm	4.0mtr	5500kg @ 60°
CS10MM4L5.0M	10mm	5.0mtr	5500kg @ 60°
CS10MM4L6.0M	10mm	6.0mtr	5500kg @ 60°
CS13MM4L1.0M	13mm	1.0mtr	9200kg @ 60°
CS13MM4L2.0M	13mm	2.0mtr	9200kg @ 60°
CS13MM4L3.0M	13mm	3.0mtr	9200kg @ 60°
CS13MM4L4.0M	13mm	4.0mtr	9200kg @ 60°
CS13MM4L5.0M	13mm	5.0mtr	9200kg @ 60°
CS13MM4L6.0M	13mm	6.0mtr	9200kg @ 60°



**SUPPLIED WITH TEST  
CERTIFICATE**



**FITTED WITH A WORKING LOAD  
LIMIT TAG**











**SUPPLIED IN A STORAGE  
PAIL, WITH THE RESELLERS  
CONTACT DETAILS DISPLAYED  
ON THE LABEL**



**ISSUED WITH INDIVIDUAL  
SERIAL NUMBERS**

**ALLOY GRADE (T80) CHAIN SLINGS  
To AS 3775.1-2014**

CHAIN DIA.    mm	SINGLE LEG SLINGS			SLINGS OF 2, 3 OR 4 LEGS				ENDLESS SLINGS			
	 Straight lift	 Shortened straight lift	 Reeved sling	 Straight sling			 Reeved sling	 Basket sling			 Reeved sling
	W.L.L Tonnes	W.L.L Tonnes	W.L.L Tonnes	W.L.L Tonnes			W.L.L Tonnes	W.L.L Tonnes			W.L.L Tonnes
6	1.1	1.1	0.8	1.9	1.6	1.1	1.5	1.5	1.2	0.8	1.7
7	1.5	1.5	1.1	2.6	2.1	1.5	2.0	2.0	1.6	1.1	2.3
8	2.0	2.0	1.5	3.5	2.8	2.0	2.6	2.6	2.1	1.5	3.0
10	3.2	3.2	2.4	5.5	4.5	3.2	4.1	4.1	3.4	2.4	4.8
13	5.3	5.3	4.0	9.2	7.5	5.3	6.9	6.9	5.6	4.0	8.0
16	8.0	8.0	6.0	13.8	11.3	8.0	10.4	14.5	11.9	8.4	5.6
19	11.2	11.2	8.4	19.2	15.8	11.2	14.5	14.5	11.9	8.4	5.6
20	12.5	12.5	9.4	21.6	17.6	12.5	16.3	16.3	13.3	9.4	18.8
22	15.0	15.0	11.3	26.0	21.2	15.0	19.5	19.5	15.9	11.3	22.5
26	21.2	21.2	15.9	36.7	29.9	21.2	27.6	27.6	22.5	15.9	31.8
32	31.5	31.5	23.6	54.5	44.4	31.5	41.0	41.0	33.4	23.6	47.3

NOTE: The quoted W.L.L is approximate and relevant to Grange Lift products.