

# LRA-VSTH 35K-RA

**Light duty swivel castor, with bolt hole fitting, with brake system 'Radstop', heavy duty wheel, with Blickle Extrathane® polyurethane tread, with steel wheel centre**

**EAN** 4047526362348  
**ID** 935484  
**Customs tariff number** 83022000



**Bracket:** LRA series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

**Wheel:** VSTH series

- tread: high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A, colour light brown, non-marking, non-staining
- wheel centre: steel



**Other features:**

- high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +70 °C, temporarily up to +90 °C, reduced load capacity over +40 °C

**Technical data:**

Wheel Ø (D)	⊘	35 mm
Wheel width	∅	27 mm
Load capacity at 3 km/h	⊞	100 kg
Load capacity (static)	⊞	250 kg
Bearing type	⊙	ball bearing
Total height (H)	⊘	50 mm
Plate Ø	⊘	43 mm
Bolt hole	⊘	11 mm
Offset (F)	⊘	15 mm
Temperature resistance min		-20 °C
Temperature resistance max		70 °C
Tread and tyre hardness		92 Shore A
Unit weight	⊞	0.2 kg
Non-marking		✓
Electrically conductive	⊞	✗
Antistatic	⊞	✗
Corrosion-resistant		✗
Heat-resistant	⊞	✗
Non-staining		✓
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

**Tread and tyre hardness**



**Rolling resistance**



**Wear resistance**



**Operating noise / floor surface preservation**

