

rolling forward...

SERIESCASTORS



PNEUMATIC CASTORS

- » Great for external use over rough, uneven & soft surfaces
- » Rugged robust wheels for tough applications
- » Good shock / impact absorbency

PLEASE NOTE: The air pressure supports the load - under-inflated tyres can result in damage to the tyres/tube/rim and potential injury to the operator or bystanders. Tyres pressures and load ratings stated in this catalogue are the maximum recommended for all usage conditions with speeds up to 12kph.

Please consult with our representative for loads/speeds in excess of those stated or where operating conditions are of an extreme nature.

FOAM FILLED CASTORS

- » Great for external use over rough, uneven & soft surfaces
- » Rugged robust wheels for tough applications
- » Good shock / impact absorbency
- » No more punctures

PLEASE NOTE - Foam filled tyres can flat spot under load and when left stationary in hot conditions. The PU foam has a memory and will return to shape.



WHEEL DIAMETER (mm)	MOUNTING TYPE	FRAME CODE	WHEEL TYPE	MAX LOAD (KG)	OVERALL HEIGHT (mm)	SWIVEL RADIUS (mm)
Ø	Ţ			Ĩ	I	
220		PZF250X4-PS	PNEUMATIC	120	257	-
265	$\mathbf{\Theta}$	PZF350X4-PS	PNEUMATIC	160	320	-
220		PZN250X4-PS	PNEUMATIC	120	257	157
265		PZN350X4-PS	PNEUMATIC	160	320	187
220		PZNW250X4-PS	PNEUMATIC	120	257	157
265	Ο	PZNW350X5-PS	PNEUMATIC	160	320	187
220		PZF250X4-FS	FOAM FILLED	120	257	-
265	\bullet	PZF350X4-FS	FOAM FILLED	160	320	-
220		PZN250X4-FS	FOAM FILLED	120	257	157
265	U	PZN350X4-FS	FOAM FILLED	160	320	187
220		PZNW250X4-FS	FOAM FILLED	120	257	157
265		PZNW350X5-FS	FOAM FILLED	160	320	187