



Live Infinitely LLC is not responsible for any damage or injury caused by incorrect installation, alteration or misuse of the kit. Have the kit professionally installed if you're not sure about the steps below. Do not jump or aggressively use. Do not allow unattended children to use it. Be Safe and remember that 18" from the ground is good height for your hammock

WARNING:

Installation of the indoor hanging kit should be completed by a qualified professional ONLY! Failure to install correctly could result in injury and or damage to personal property! The hanging kit includes the hardware to attach to wooden structures only. Sheetrock/ drywall will not be strong enough to hold the weight of a person. Make sure that your bolts are secured into a wall stud or surface capable of holding you and your hammock!

If you have questions please watch our installation video at www.liveinfinitely.com or contact us directly for assistance

STEP 1

You will need to choose the walls where you are going to hang your hammock at. For Live Infinitely hammocks the ideal distance would be about 9 ft between walls and about 55" off the ground. This will vary between hammocks but it's best to lay your hammock out to determine the distance apart you need it. You can always add rope or chain if the walls are further apart than your hammock. Have someone help you hold the hammock in place to determine the height and distance apart you would like

STEP 2

Locate your wall studs! If you're using a stud finder this step is easy and you can go to step 3 now. If not a few tips for you to use. Start knocking on your wall moving horizontally as you do it, you will notice a "hollow" sound when away from the stud and a firmer sound when you're on the stud. Normally electrical outlets are on wall studs. Doors and window frames will always be reinforced and attached to studs. If you can't locate a wall stud DO NOT hang the kit, consult a professional. **Drywall WILL NOT hold the weight**

STEP 3

Determine the height you would like, taking into account if you will be adding rope you may need it slightly higher for the length of the rope then Mark and drill the Center of your wall stud. Normally studs are 1 1/2" thick, mark each side and use your small drill bit (7/64") to drill a small test hole and make sure wood shavings come out showing you hit the stud. Then use your 9/32" drill bit to drill the final hole about 3" deep.

STEP 4

Tighten your bolts down. The included bolts are for WOOD use only. Slide the bolt through the anchor and use the 9/16" wrench to tighten the anchor snugly. Do not over tighten and compress the drywall excessively.

STEP 5

Hook up your hammock and test your work out! Use the included carabiners or the original hammock ones. Slowly add weight to test before fully entering the hammock! Don't forget you can add rope or chain to adjust for the perfect hang


STEP 6

Enjoy Your Hammock ALL YEAR NOW!

Install Instructions & Video Available By Visiting

WWW.LIVEINFINITELY.COM/HANGER-MANUAL

Tools Required



Tape Measure



7/64" & 9/32"
Drill Bits



Power Drill



9/16" or 14mm Wrench



Suggested:
Stud Finder

