



FF13060

SPECIFICATIONS

Reticle type	mil dot
Reticle color	red/green
Reticle brightness settings	0-5
Finish/color	matte black
Magnification	1-4x
Objective lens diameter	24mm
Eyepiece diameter	36mm
Exit pupil diameter	12.3 - 6.2 mm
Eye relief	120 - 105 mm
Field of view (m@100m)	27.2 - 7.34
Field of view (ft@100yds)	88.3 - 23.8
Diopter adjustment	+/- ~3
Tube diameter	30mm
Parallax settings	100yds
Windage/Elevation (MOA)	120
MOA adjustment (one click)	1/2
Maximum recoil (G's)	800
Battery type	CR2032
Battery life	80-150 hours
Battery voltage	3V
Focal plane	second
IP Standard (water rating)	IPX6 - weatherproof
Body material	aluminum
Lens material/type	glass
Lens coatings	AR blue
Mount type	weaver
Operational temp (°F)	0-120
Dimensions (mm)	225 x 68 x 56
Weight	14.2oz

Close Combat 1-4x24 Riflescope

INCLUDED ACCESSORIES

- cleaning cloth
- mounting rings
- battery

FEATURES

- Mil-dot reticle
- Red/green reticle illumination
- Fully mutli-coated lenses
- Weatherproof, fogproof, shockproof
- Compact and lightweight
- Variable 1-4x magnification
- Exposed turrets
- Hard anodized finish
- Fast focus eyepiece