



# PISTOL FLASHLIGHT USER MANUAL

English / Français / Español / Deutsch/ Italiano/ Русский язык/ Polski

# VICTORY JUSTIFIES EVERYTHING

Whether you are in a fast-paced combat situation or defending yourself and your home, Firefield™ will be by your side, preparing you for victory. Firefield™ offers quality products with outdoor enthusiasts and paintball fanatics in mind. Whether your weapon of choice is paintball, airsoft, AR15, shotgun or pistol, Firefield™ can accommodate your preference. Firefield™ will provide you with high quality and durability for a fraction of competitor pricing. Firefield™ products consist of boresights, flashlights, laser sights, reflex sights, rails, mounts, magazines, binoculars and other shooting accessories.



[www.fire-field.com](http://www.fire-field.com)

Pistol Flashlight .....	1- 5
Pistol Flashlight .....	6- 11
Pistol Flashlight .....	12- 16
Pistol Flashlight .....	12- 16
Pistol Flashlight .....	12- 16
Pistol Flashlight .....	12- 16
Pistol Flashlight .....	12- 16

- English
- Francias
- Español
- Deutsch
- Italiano
- Русский язык
- Polski

### Features:

- Lightweight/Compact Design
- 120 Lumen Brightness
- Easy-Access Slide Switch

### Technical Specifications:

Bulb type	White LED
Output Power	120 Lumens
Battery life	20 hours
Battery type	1 xCR123A
Waterproof Rating	IPX4
Weight	2.5oz
Length	78mm



Fits Pistols and Rifles  
with weaver or  
picatinny rails.

### DIAGRAM

1. Bulb assembly
2. Flashlight body
3. On/off switch
4. Weapons mount





## BATTERY INSTALLATION

The Firefield pistol flashlight uses 1 CR-123A battery (included).

To insert or remove the battery:

- 1) Rotate the bulb assembly (1) counter clockwise until it separates from the flashlight body (2).
- 2) Insert the CR123A battery into the flashlight body (2) with the negative end first.
- 3) Replace the bulb assembly (1) into the flashlight body (2). To tighten, rotate the bulb assembly clockwise until fixed firmly. Do not over tighten.



## SWITCH OPERATION

Slide switch:

- 1) To turn the flashlight on, press the slide switch to the right.
- 2) To turn the flashlight off, press the slide switch to the left.

## MOUNTING

- 1) Using the Allen wrench, loosen the mounting bolt on the weapons mount (4).
- 2) Position the flashlight onto your firearm's mount and tighten the mounting bolt.

## STORAGE

Make sure that your Firefield pistol flashlight is turned off and securely attached to your firearm before storing.

## MAINTAINANCE

The flashlight may be cleaned using a soft cloth and water, or a gun cleaning solvent when the product has been exposed to dirt, dust, or residue. Clean the lens using a soft cloth dipped in water or denatured alcohol. Maintain threads and O-rings by applying silicon based grease.

## WARNING

Before handling the Firefield pistol flashlight, read and understand the contents of your firearm's manual. Follow all standard safety precautions and procedures during firearm operation.

## FIREFIELD LIMITED WARRANTY

- NEVER point the flashlight directly at, or into, an eye. This may cause damage to the eye, or blindness. The flashlights produce enough light to identify an individual without direct illumination to the face.
- Avoid looking directly into the flashlight's beam.
- Avoid shining the flashlight into mirrors or other reflective surfaces.
- Avoid hitting or dropping the unit.
- ALWAYS check that the chamber of your weapon is clear before mounting or dismounting the flashlight.
- ALWAYS remove the flashlight when cleaning, or performing other maintenance, on your firearm.
- The flashlight should be tested during periods of non-use to make sure it is still operating properly.
- NEVER place the flashlight bulb side down on a surface while it is turned on. The bulb generates heat that can damage the unit or the surface it is on.

Failure to follow standard firearm safety precautions and procedures, as well as the above warnings, is dangerous and may result in serious injury, damage to property, or death.



Your product is warranted free of defects in materials and workmanship. In the event of a defect under this warranty, we will, at our option, repair or replace the product. Lasers, red dots, and holographic imaging devices are warranted to be free from defects for a period of 3 years. However, light bulbs, batteries and other consumable components are not applicable to this warranty. This warranty does not cover damages caused by misuse or improper handling. Also, this warranty is null and void if modification or maintenance is provided by someone other than the manufacturer.

If you are sending in a product for a warranty repair, you will be required to fill out a RA request form, which can be found at the brand's website. Once the form has been received and processed, you will receive a confirmation email containing your RA number and a PDF Return Form. The Return Form must be filled out completely, and mailed in, with your product. In order for your repair to be successfully fulfilled, be sure to closely follow all instructions outlined by the Return Form. If any of the aforementioned instructions are not properly followed, your request cannot be processed and the product will be held until you are contacted, and proper documentation is received.

To receive a RA number for warranty service or out-of-warranty repair, or need further information regarding warranty details and information, visit [www.fire-field.com](http://www.fire-field.com).

This warranty is non-transferable and is only valid if the product is registered within 30 days after the product has been purchased. To register your product, go to the brand's website. Warranty details and updates, including specific warranty coverage outside the United States, are located online, along with information regarding any shipping costs and/or handling fees. Registering online may also provide additional coverage and faster warranty service.

*\*Warranty varies by country. See website for details.*