SIGHT IMARK[®]

SPECIFICATIONS

Magnification (x)	1x
Objective (mm)	34x25 (mm)
Field of View (m @ 100m)	36
Coating	AR red
Water Resistant	Yes
Eye relief	Infinite
Reticle	Multi 4 patterns
MOA Adjustment	1 Click
Battery life	25 hours
Power supply	CR1620
Battery voltage	3V
Max recoil	Up to .50 Caliber
Operating Temp.	-10 to 50 C
Dimensions (in)	3.7x1.8x2.4
Weight (oz)	5.7
Brightness Settings	1 – 5 and off
Construction	Aircraft Grade Aluminum

The **Sightmark Ultra Shot** reflex sight utilizes the ever popular 4 different reticle patterns and adjustable brightness settings, as well as the widest field of view in its class!

Ultra Shot (dove tail) FEATURES

Precision accuracy	
Interlok™ internal locking system	
🔶 Composite body with metal protective shield	
🔶 Wide field of view	
Perfect for rapid fire or moving target shooting	
Multi-reticle (4 patterns)*	
🔶 Adjustable reticle brightness	
Parallax corrected and Unlimited eye relief	
🔶 11 mm dove tail mount	
Able to withstand heavy recoil calibers	
🔶 Lightweight, Water resistant, and Shockproof	
🔶 Low power consumption	
INCLUDED	
🔶 Neoprene cover	
🔶 Adjustment tools	
🔶 Batteries	

🔶 Limited Lifetime Warranty

SM13005-DT

www.sightmark.com