# SIGHT I MARK<sup>®</sup>









#### Mil-Dot Reticle

SPECIFICATIONS

SPECIFICATIONS	
Water / Shock proof	Yes
Reticle color	black red green
Illuminated	yes
Reticle brightness	0-11
Finish/color	matte black
Magnification (x)	6-25
Objective diameter	56 mm
Eyepiece diameter	36.5mm
Field of view (m @100m)	5.8-1.5
Field of view (ft @100yd)	17.3-4.4
Diopter adjustment	2 to -3
Tube diameter (mm)	35mm
MOA adjustment	1/4" one click
Maximum recoil (G's)	1200G
Battery type/Voltage	CR2032 / 3V
Battery life (hours)	80-150
Focal plane	2nd
IP Standard (water rating)	IPX4
Mount	weaver
Operating temp. (C)	-20-60
Dimensions (mm)	530x130x95
Body material	HI-Grade Aluminum
Weight	25.4oz

Duplex Reticle

## **Triple Duty 6-25x56 Riflescope**

**INCLUDED** 

Set of 35 mm rings

Limited Lifetime Warranty

### FEATURES

- Precision accuracy
- Adjustment lock
  - Wide field of view
- Precision multicoated optics
- Internal lit reticle
- 1/4" MOA locking turrets
- Easy focusing knob, and Side diopter adjustment
- Lightweight, Waterproof, and Shockproof

#### The Sightmark 6-25x56 Triple Duty Riflescope

is equipped with an illuminated red/green Circle Dot Duplex reticle that is based on the World War II German Sniper Rifle, designed for moving targets and quick acquisition.

# SM13019 SM13019DX SM13019CDX SM13019MDD

www.sightmark.com