

SIGHT MARK®



SPECIFICATIONS

Reticle type	VXR-L
Reticle	etched
Reticle color	black and red
Reticle brightness settings	0-11
Finish/color	matte black
Magnification	3x
Objective lens diameter	32mm
Eyepiece diameter	39mm
Exit pupil diameter	10.6mm
Eye relief	76.2mm
Field of view (m@100m)	14.73
Field of view (ft @100yd)	44.2
Diopter adjustment	+3 to -3
Tube diameter	25.4mm / 1in
Parallax setting	30 yds
Windage/Elevation adjustment range	80 MOA
MOA adjustment (one click)	1/2
Maximum recoil (G's)	800
Battery type	CR2032
Battery life	25-1000 hours
Battery voltage	3V
IP Standard (water rating)	IP66 - weatherproof and dustproof
Body material	Aluminum
Lens material	glass

Core SX 3x32 Crossbow Scope

Lens coating	multi-coated
Operating temp	0 to 120 °F
Dimensions mm	228 x 66 x 38
Weight	14oz

FEATURES

- ⦿ Tuned for 320fps crossbow speeds
- ⦿ Red illuminated etched reticle
- ⦿ 11 reticle brightness settings to adapt to range of lighting environments
- ⦿ Reticle holdover points out to 60 yards
- ⦿ Killzone rangefinding for large game
- ⦿ Designed to withstand crossbow recoil
- ⦿ Shockproof, fogproof, weatherproof
- ⦿ Compact and lightweight
- ⦿ Fully multicoated optics

INCLUDED

- ⦿ Neoprene scope cover
- ⦿ 1" Scope rings

Engineered with a red/black VXR-L reticle with 11 brightness settings for use in various lighting environments, and arrow drop compensation for shot placement, the **Sightmark® Core™ SX 3x32 Crossbow Scope** is designed for large-sized game such as elk or moose.