

SIGHT MARK®



SPECIFICATIONS

Reticle type	5 moa dot
Reticle color	green
Reticle brightness	1-5 and off
Finish/color	matte black
Magnification	1x
Objective lens size	23x16mm
Eye relief	unlimited
Field of view	15.7 (m@100m)
Field of view	51.5 (ft @100yd)
Parallax free @ (yds)	10yds to infinity
Windage MOA	150
Elevation MOA	205
MOA adjustment (one click)	1
Maximum recoil (G's)	1000
Battery type	CR1620
Battery life	20-10,000 hours
Battery voltage	3V
Waterproof IP Standard	IPX4 - weatherproof
Body material	Aluminum
Lens coatings	AR Green
Mount type	weaver/picatinny
Operating temp (°F/°C)	0 to 120 / -17 to 49
Dimensions (mm) with protective shield	48.6 x 34.8 x 40
Dimensions (mm) with protective shield and riser	48.6 x 34.8 x 56.9
Weight w/ protective shield and low profile mount	3.3oz
Weight w/ protective shield and riser mount	4oz

Mini Shot Pro Spec Green

FEATURES

- ✦ Click adjustable windage/elevation
- ✦ External battery compartment prevents need to rezero after battery replacement
- ✦ Protective shield
- ✦ Digital switch operation
- ✦ 5 reticle brightness settings
- ✦ 5 moa green dot
- ✦ Parallax corrected for precision accuracy
- ✦ 1x power for "both eyes open" usage
- ✦ Low power consumption
- ✦ Lightweight and shockproof
- ✦ Scratch resistant lenses
- ✦ Weatherproof

INCLUDED

- ✦ weaver/picatinny mount
- ✦ Protective shield
- ✦ low profile mount
- ✦ riser mount (lower 1/3 cowitness)
- ✦ battery
- ✦ allen wrench
- ✦ lens cloth

Designed for shotguns, rifles, and pistols, the **Sightmark® Mini Shot Pro Spec™** with green reticle is equipped with an advanced optical system with dual-pane glass, a scratch-resistant lens, and a battery life up to 10,000 hours.