




TOOLS AND ACCESSORIES F	PART NUMBERS
DESCRIPTION	PART NUMBER
PROGRAMMING SHUNTS (RED) PROGRAMMING SHUNTS (WHITE)	382811-9 382811-0
LACING BAR 6IN (152.4MH) LACING BAR 3IN (76.2MM)	LB-17500 LB175-3
DB25 MALE WITH SOLDER PIN 25 PIN DSUB METAL HODD	DS-25P/T DM-25C







-17.500 [444.500]-

REAR VIEW

....a p(.....a p(...

SIGNAL GROUND-BINDING POST

## **A** Bittree

PATCHING SYSTEM audio, video, serial data 600 WEST ELK AVENUE GLENDALE, CA. 91204 TEL 818 500-8142 FAX 818 500-7062 WWW.BITTREE.COM

DATA CONTAINED IN THIS DOCUMENT IS PROPRIETARY AND SHALL NOT BE DISCLOSED, COPIED OR USED FOR PROCUREMENT OR MANUFACTURING WITHOUT EXPRESS WRITTEN PERMISSION OF BITTREE INCORPORATED

DWG. NO.:

0

3.470 [88.138]

B96DCHNSSTD25M20U7B

PART NO.:

B96DC-HNSST/D25 M20U7B

ORDER NO. 969S342

SERIES: 969-S

PANEL HEIGHT:

2 RU (3.470") [88.138 MM]

DESIGNATION: DS800-10-ASSY

FINISH:

BLACK POWDER COAT

PANEL MATERIAL:

3/16" [4.7625 MM] ALUMINUM

JACK SCREWS : M3-0.5X12FLPH-S

LAYER (DS\_INSERT) IS PROVIDED FOR THE CREATION OF LEGEND STRIPS FOR THIS PATCHBAY. THE RED OUTLINE MATCHES THE SIZE

OF INSERT.
PLEASE NOTE THE SAFE VIEW AREA
IS PRINTED ON THE RIGHT SIDE
OF THE DESIGNATION INSERT.

DWG. SCALE: FULL

PDF. SCALE: NONE

ALL POSSIBLE CARE HAS BEEN TAKEN IN PREPARING THIS SET OF DRAWINGS. STATEMENTS AND SPECIFICATIONS ARE BELIEVED TRUE BUT CANNOT BE GUARANTEED AND THEREFORE WE ARE NOT RESPONSIBLE FOR ANY INACCURACIES. THIS DOCUMENT SHOULD BE USED AS THE BASIS FOR DESIGN OR TO ESTABLISH SPECIFICATION LIMITS.

BITTREE RESERVES THE RIGHT TO CHANGE OR ALTER SPECIFICATIONS OR MATERIALS WITHOUT NOTICE, PROVIDED THE FUNCTION AND AND PERFORMANCE OF THE PRODUCT REMAINS REASONABLY SIMILAR OR IS IMPROVED.

