

LED BUG EYE EMERGENCY LIGHTING FIXTURE

C&C Lighting Inc. Technical Data Sheet





PRODUCT FEATURE

White thermoplastic emergency unit. Construction - Injection-molded, flame-retardant, high impact, thermoplastic housing with snap-fit design components for easy installation. Universal J-box pattern. Track and swivel arrangement permits full range of lamp adjustment. Not intended for ceiling mounting. Lamp Data - The typical life of the LED is 10 years. Electronics - Dual-voltage input 120V or 277V AC. Emergency unit provided with test switch, status indicator and rechargeable battery. Maintenance-free battery provides 90 minutes of emergency power.

CONSTRUCTION

Injection-molded, V-O flame- retardant, high-impact thermoplastic housing. Dual voltage 120/277VAC. Two 1.8W lamp heads provide emergency lighting for 90 minutes. Test switch and status indicator provided for visual and manual means of monitoring system operation. Fixture uses 5.4 watts in non emergency mode. Two-year warranty.

| | |
|---------------|-----------------------------|
| BRAND | CCR Inc. |
| PART NUMBER | EU2 LED M12 |
| POWER | 5.4W |
| VOLTAGE | 120-277V |
| TYPE | Emergency light-Adj. Optics |
| DIMENSION | 146.1x114.3x257.3mm |
| COLOUR FINISH | White |
| DESCRIPTION | 2-headed LED Emergency Unit |



