




### SPECIFICATIONS

- **Materials:** Aluminum extrusion with copper bus wire.
- **Electrical:** 20 Amps rated, 120V. It is common practice to use
- **tracks at 80% capacity to insure compatibility with dimmers and**
- **connectors (1920W maximum).**
- **Mounting:** Can be installed on drywall, or suspended ceilings.
- **Standards:** UL & CUL listed

### ACCESSORIES




Track Center Feed-blk



TRACK T-CONNECTOR-wht



TRACK L-CONNECTOR-wht



Track LIVEEND-wht

### ORDER INFORMATION

Name	SKU
TRACK T-CONNECTOR-wht	608
TRACK T-CONNECTOR-blk	246
TRACK L-CONNECTOR-wht	336
TRACK L-CONNECTOR-blk	1489
Track LIVEEND-wht	1481
Track LIVEEND- blk	337
Track Center Feed-wht	1472
Track Center Feed-blk	338
12 Track -blk	897
12 Track -wht	898
8 Track-blk	1358
8 Track-wht	1359
4 Track-blk	1469
4 track-wht	1470

### LIGHTING OPTIONS



Universal Track Holder -BLC



Universal Track Holder -WHT



TRACK LIGHT 3CCT-WHT



TRACK LIGHT 3CCT-BLC