



GPS L1/L2 Amplifier System

GPS Amplifier Assembly, GPS Antennas,
Cabling, other options and accessories

Part Numbers

GPS L1/L2 Amplifier System



Includes:

1. Amplifier Assembly *(Choose One)

GPSRKL12-P110/5-NF

GPSRKL12-P230/5-NF

2. Active Outdoor Antenna

L1L2-2GA-PM-NF

3. Cable Assembly (50ft/15.25m)**

C240-50-NM

4. Coax Lightning Protection

(Optional)

* The Amplifier Assembly includes a GPS amplifier, passive antenna and panavise mount. Other Power Options, Antenna DC and Connector types are available. Call Sales for Details. Other Power Options, Antenna DC and Connector types are available. Call Sales for Details.

**Additional cable lengths available

This GPS L1/L2 amplifier system operates by receiving GPS satellite signals with an antenna located outside the structure/building/hangar and bringing the signal inside or under a covered space. It is a low power L1/L2 GPS amplifier system that is often used for system testing, initialization and product demonstration. This equipment is not used for indoor navigation. The GPS position of any device operating from the transmitted signal would reflect the position of the active outdoor antenna, instead of the actual GPS receiving device.



GPS LIVE INSIDE

GPS Source, Inc.
64 N. Mission Drive
Pueblo, West, CO 81007
T: 719.561.9520
F: 719.565.0890
sales@gpssource.com
www.GPSSource.com

An AS9100 Certified Company

GPS Source, Inc. | 64 N. Mission Drive, Pueblo, West, CO 81007 | T: 719.561.9520 | F: 719.565.0890 | sales@gpssource.com | www.GPSSource.com

1581-MS-GPSRKL1L2-01no