


# SINGER AUTOMATIC ZIGZAGGER



THE SINGER MANUFACTURING COMPANY

Form 20817 (156)

# INSTRUCTIONS FOR USING

Printed in U.S.A.

# SINGER

# AUTOMATIC ZIGZAGGER

No. 161102 on SINGER\* Sewing Machines of Classes 15, 201, 221 and 1200 and

No. 161103 on Machines of Class 301

This wonderful SINGER fashion aid will enable you to produce an infinite variety of attractive ornamental designs merely through the interchange of the different Stitch Patterns and the adjustment of the bight and stitch length. Such decorative effects as applique, scalloped edges, border designs, as well as blind stitched hems and simple mending can be produced with this attachment on women's and children's clothing, lingerie, linens, draperies and an unlimited array of other garments and household items.

With the flick of a lever, plain sewing may be done without removing the zigzagger from the sewing machine.

Copyright © 1956 by The Singer Manufacturing Company

\*A Trade Mark of THE SINGER MANUFACTURING COMPANY



# TO FASTEN ZIGZAGGER TO MACHINE




Fig. 2. Zigzagger Fastened to Machine

- Raise presser bar, remove presser foot and thumb screw from machine.
- Guide zigzagger into position from rear of machine so that fork A straddles hub of needle clamp, and securely fasten, with screwdriver, shank  ${\bf C}$  of zigzagger to presser bar with clamping screw  ${\bf K}.$

# STITCH PATTERNS

Four Stitch Patterns are furnished with the Zigzagger for producing the basic designs

shown on pages 4 to 7.

Each design can be greatly varied by changing the bight and stitch settings as indicated in the illustrations.

Combinations of the designs made by the Stitch Patterns may be used to produce many pleasing ornamentation

### ZIGZAG STITCH PATTERN

appliqueing, tucking, joining or inserting lace, reinforcing plain or welt seams, making invisible seams in all over lace or embroidery and seam finishes. It is also useful for making border designs by varying bight and stitch settings. Many interesting designs for women's and children's clothing, as well as linens and curtains may be developed by using different adjustments.

(A) To lock the pattern upon completion of the stitching, set attachment in straight stitching position and sew three or four very short stitches.



Fig. 3. Zigzag Stitch patterns made by changing bight and stitch settings as indicated

(B) When sewing on soft, sheer, textured or loosely woven fabrics, use a backing of one or two thicknesses of crisp lawn, tarlatan or organdy and cut away the backing when design is completed.

(C) When a pattern is to be stitched close to the edge of the fabric, a straight line of stitching should be made to stay the fabric. Regulate bight and stitch to produce the most pleasing results. The ornamental stitch may be sewn over the straight stitching.

# BLIND STITCH PATTERN

Blind Stitch Pattern 161001 / produces a curved line and one long sideward stitch at start and at completion of curve. Width and length of curve depend on bight and length of stitch. This Stitch Pattern is ideal for hems, for overedging very narrow hems, for overedging seam edges, for staying fringed edges and drawn work, and for stitching tucks. The tiny scallops are decorative and, by combining with other Stitch Patterns, many attractive effects can be obtained for borders.

Direction of stitching is left to right.

Follow instructions A and B on page 4 when this pattern is used for decorative stitching.




Fig. 4. Blind Stitch patterns made by changing bight and stitch settings as indicated

#### DOMINO STITCH PATTERN

(A) To lock the pattern upon completion of the stitching, set attachment in straight stitching position and sew three or four very short stitches. To deposit the pattern of the stitching position and sew three or four very short stitches.



Fig. 5. Domino Stitch patterns made by changing bight and stitch settings as indicated

(B) When sewing on soft, sheer, textured or loosely woven fabrics, use a backing of one or two thicknesses of crisp lawn, tarlatan or organdy and cut away the backing when design is completed.

(C) When a pattern is to be stitched close to the edge of the fabric, a straight line of stitching should be made to stay the fabric. Regulate bight to produce the most pleasing results. The ornamental stitch may be sewn over the straight stitching.

# ARROWHEAD STITCH PATTERN

Arrowhead Stitch Pattern 161003 WM WM produces a design which is ideal for ornamental purposes. The size of Arrowhead is determined by the bight setting and texture of material. Stitch setting should be short (approximately No. 30) for a solid effect. For any desired spacing between Arrowheads, pull lever B, Fig. 10, page 10 forward for straight stitching and count number of stitches for a given space. When desired spacing is attained, push lever B back for zigzag stitching. Arrowhead is most distinct when bight is set at W and stitch regulator at No. 30.

Direction of stitching is left to right.

Follow instructions A, B and C on page 6.




Fig. 6. Arrowhead Stitch patterns made by changing bight and stitch settings as indicated

healthing of the Zigzag. Doning and Arrowhead patterns and the cames passion for all other parterns. It also centers the foot for facility slithing.

Fig. B. Removing or

7

#### TO REMOVE AND REPLACE STITCH PATTERNS

- 1. RAISE PRESSER BAR.
- Lift and swing back cover as shown in Figs. 7 and 8.
- 3. Lift out Stitch Pattern.



Fig. 8. Removing or Replacing Stitch Pattern



Fig. 7. Lifting Cover to Remove Stitch Pattern

- Select desired Stitch Pattern, place it in position and turn it in a clockwise direction until it drops in place.
- 5. Close cover.
- 6. Turn stitch pattern so that arrow M, Fig. 9 points to line N on top of cover. This setting denotes the beginning of the Zigzag, Domino and Arrowhead patterns and the central position for all other patterns. It also centers the foot for straight stitching.

#### TO ADJUST BIGHT OR SIDEWISE MOVEMENT OF PRESSER FOOT

The setting of bight scale **O**, marked with the letters N (for narrow bight), M (for medium bight) and W (for wide bight), determines the width of the design.

To adjust bights

- 1. RAISE PRESSER BAR.
- 2. Loosen lock screw J.




Fig. 9. To Regulate Bight and to Set Stitch Pattern to Start Design

- Grasp handle G and slide the regulator forward or backward until desired bight is obtained.
- 4. Tighten lock screw J.

The length and width of all designs depend on the stitch and bight settings.

9

# TO ADJUST ZIGZAGGER FOR STRAIGHT STITCHING

- 1. Stop machine when zigzagger foot is in central position with arrow M, Fig. 9 opposite line N.
- 2. Pull lever B, Fig. 10 toward you. Plain sewing can then be done.

To resume zigzag stitching, push lever away from you.



Fig. 10. To Adjust Zigzagger for Straight Stitching

# THREADS

No special threading is required. No. 50 mercerized cotton and size A silk threads may be used. For these threads be sure to use size 14 needle. Finer mercerized embroidery cotton threads will produce improved effects.

# TENSIONS

When making solid designs, such as zigzag satin stitch, domino or arrowhead, operate machine with a lighter top tension than for ordinary sewing.

# PRESSURE ON FOOT OF ZIGZAGGER

Slightly less pressure than for normal sewing will be required to allow for proper sidewise movement of fabric when making intricate stitch patterns. The amount of pressure should be varied according to the surface and texture of the fabric. Pressure is regulated by turning knurled thumb screw on top of machine arm in counter-clockwise direction to reduce pressure, or clockwise to increase pressure.

# SEWING SPEED

Operate sewing machine slowly and hold material loosely so that it moves freely with zigzagger foot.

Do not operate sewing machine without material underneath zigzagger foot.

# MARTIAN ROTHESUITABLE MATERIALS CORN EMOISED

Firm cotton fabrics such as lawn, organdy, broadcloth, poplin, chambray, Indian Head, denim, polished cotton, cotton taffeta, sateen and gingham are suitable for use with the zigzagger, linen, sheer woolen, silk, fell and synthetic fabrics of firm weave are also effectively stitched.

#### TO PREPARE FOR ORNAMENTAL STITCHING

Lay both threads back under presser foot diagonally across the feed to the right or left so that when the presser foot is lowered, the threads will be firmly held between the feed, material and zigzagger foot.

#### PREPARATION OF MATERIAL


Always test stitch on a scrap piece of the material to which design is to be applied, since the bight may have to be adjusted to suit the weave, the texture or finish of fabric. You may find it more satisfactory to use one or two plies of backing or stay of crisp lawn, tarlatan or organdy with some sheer materials or with other materials if the design is on the bias or slightly off grain. The backing is basted to underside of material and then, when design is completed, trimmed away close to design.


For making border designs, mark parallel lines or scallops on fabric with a light brush of the pencil or with chalk. Some basting adjacent to the edge is recommended to avoid creepage of fabric.


# TO START STITCH PATTERN


Set Stitch Pattern so that arrow M, Fig. 9 is directly opposite line N on cover of zigzagger. If, for, any reason (such as thread breaking or bobbin running out of thread), it is necessary to start in middle of  $\alpha$  design, stitch on a scrap of material until that point in design is reached. Then place work under needle at exact point in design. Continue























The SINGER Automatic Zigzagger is only one of many attachments available at your SINGER SEWING CENTER ...attachments which will enable you to accomplish a great variety of work with a minimum of time and effort... attachments which can give your home sewing that smart professional look.

YOUR SINGER SEWING to help you with instruction Dressmaking and Home Decord hundred and one other help supplies. Our finishing servicustom Made Belts, Button and Here too you will also find



YOUR SINGER SEWING CENTER stands ready to help you with instructions and advice on Home Dressmaking and Home Decorations. You will also find a hundred and one other helpful sewing services and supplies. Our finishing services include Hemstitching, Custom Made Belts, Button and Buckle Covering, Picoting. Here, too, you will also find the widest selection of thread, zippers, buttons and other notions.

Drop in and get acquainted at your

SINGER SEWING CENTER



History History History History History History History History History History