To remove the work, stop the machine with the thread take-up lever at its highest point, raise the presser bar, hold the end of the seam firmly so as to prevent the threads from drawing the hemstitching together, then pull the work back about two inches and cut the threads close to the material.

Remove the hemstitching attachment from the machine, replace the regular presser foot and retighten the needle thread tension.

Fold the upper piece of c'oth back on itself along the line of stitching, then fold the lower piece of cloth back on itself along the line of stitching, and gently pull the two pieces of cloth away from each other, thus bringing the hemstitching to view.



Fig. 5

Hemstitching with Line of Ordinary
Stitching at Each Side

Then stitch down each side of the hemstitching in the ordinary manner, as shown in Fig. 5, placing the lines of stitching as close as possible to the line of hemstitching.

For hemstitching, the best results will be obtained by using fine thread. Nos. 60 or 70, or finer are recommended.

Form 8899 November, 1922

## INSTRUCTIONS

FOR USING

## SINGER HEMSTITCHING ATTACHMENTS

28915 AND 28986

ON

## SINGER SEWING MACHINES

15, 66, 115, 127 AND 128

FOR FAMILY USE

When Requiring Needles, Oil, Parts or Repairs for Your Machine



Lock for the Red "S" There are Singer Shops in Every City

## THE SINGER MANUFACTURING CO.

Copyright, U. S. A., 1922, by The Singer Manufacturing Co.
All Rights Reserved for all Countries
PRINTED IN U. S. A.

www.Singer-Featherweight.com




Fig. 1 Hemstitching Attachment 28915 for Machines 15, 115, 127 and 128

Remove the regular presser root from the machine, and fasten the hemstitching attachment in its place as shown in Figs. 3 and 4, being careful to see that the needle passes through the centre of the needle hole in the attachment before firmly tightening the thumb screw.




Fig. 2.

Hemstitching Attachment 28986
FOR Machine 66




Fig. 3
Hemstliching Attachment 28915
Fastened in Position on Machine 127

Having secured two pieces of cloth, place one piece of cloth under the separator blade (A, Figs. 1 and 2) and back under the presser foot (B, Figs. 1 and 2) of the attachment. Then pass the other piece of cloth over the separator blade (A) and back under the presser toot (B) of the attachment. Slightly loosen the needle thread tension. Lower the presser bar and stitch the two pieces of cloth together, running the machine at a moderate speed.



Fig. 4

Hemstitching Attachment 28986
Fastened in Position on Machine 66