

Material Safety Data Sheet (MSDS) Report

MSDS Number: SDS201712211055

Applicant: Yixing Xinchi Energy Technology Co., Ltd.

No.82 Xinzhong Road, Xinzhuang Street, Yixing City, Jiangsu Province, 214200, China.

Sample Description:		
Product name	:	Polymer Lithium-Ion Battery Pack
Battery model	:	D09
Nominal voltage	:	24V
Nominal capacity	:	6Ah/144Wh
Battery weight	:	-
Product dimension	:	L: 544mm, W: 116mm, T: 48mm
Data reviewed	:	Jan 14, 2022

Shanghai Ruifu Co., Ltd. did not test, certify, or approve the product described in this Material Safety Data Sheet (MSDS), and all information in this MSDS was provided by the applicant or was reproduced from publically available regulatory data sources. Shanghai Ruifu Co., Ltd. makes no representations or warranties regarding the completeness or accuracy of the information in this MSDS and disclaims all liability in connection with the use of this information or the product described in this MSDS. This MSDS was generated in accordance with requirements of OSHA Hazard Communication Standard 29 CFR 1910.1200 (OSHA HazCom 2012), for more details please refer to the following attached pages. This report shall not be reproduced except in full, without the written approval of Shanghai Ruifu Co., Ltd.

Approved By:

U

Pingo Zhang, Manager On behalf of Shanghai Ruifu Co., Ltd.



Product name: Polymer Lithium-Ion Battery Pack D09 Revision Date: 14/01/2022 Version: 6.0 MSDS Number: SDS201712211055 Page: 1 of 10

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier Product name	: Polymer Li	thium-Ion Battery Pack
Battery model	: D09	
Nominal voltage	: 24V	
Nominal capacity	: 6Ah/144W	h
Battery weight	: -	
Physical dimension	: L: 544mm,	W: 116mm, T: 48mm
Recommended use of the chemical and restrictions on use Identified use : Power supply for electronic device.		
Details of the supplier of the safety data sheet Yixing Xinchi Energy Technology Co., Ltd. No.82 Xinzhong Road, Xinzhuang Street, Yixing City, Jiangsu Province, 214200, China.		Emergency telephone number Tel: +86-510-87560105 or contact your local emergency center. Product Information Tel: +86-510-87560105 E-mail: Chenpeng422@sina.com

SECTION 2. HAZARDS IDENTIFICATION

This product containing lithium-ion battery is an article pursuant to 29 CFR 1910.1200 and, as such, is not subject to the OSHA Hazard Communication Standard requirement(HCS2012). The information contained in this Material Safety Data Sheet contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.

As a solid, manufactured article, exposure to hazardous ingredients is not expected with normal use. The potential for exposure should not exist unless the battery leaks, is exposed to high temperatures or is mechanically, electrically or physically abused/damaged. If the battery is compromised and starts to leak, based upon the battery ingredients, the contents are classified as hazardous.

The following GHS hazardous classification are derived based on the internal ingredients of battery under extreme exposure scenarios, such as breakage, leakage or being abused.

Product name: Polymer Lithium-Ion Battery Pack D09 Revision Date: 14/01/2022 Version: 6.0 MSDS Number: SDS201712211055 Page: 2 of 10

GHS-Classification

Hazard classification	Flammable solids, Category 1 Flammable solid. Substances and mixtures, which in contact with water, emit flammable gases, Category 2 In contact with water releases flammable gases. Skin sensitisation, Category 1 May cause an allergic skin reaction. Carcinogenicity, Category 2 Suspected of causing cancer. Specific target organ toxicity - repeated exposure, Category 2, Inhalation May cause damage to organs through prolonged or repeated exposure if inhaled.	
GHS-Labelling		
Symbol(s)		
Signal word	: Danger	
Hazard statements	: H228 H261 H317 H351 H373	Flammable solid. In contact with water releases flammable gases. May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure if inhaled.
Precautionary statements	P240 P241 P260 P272 P280 Response:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not allow contact with water. Handle under inert gas. Protect from moisture. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection. IF ON SKIN: Wash with plenty of water.

Product name: Polymer Lithium-Ion Battery Pack D09 Revision Date: 14/01/2022 Version: 6.0 MSDS Number: SDS201712211055 Page: 3 of 10

P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P335 + P334	Brush off loose particles from skin. Immerse in cool water/ wrap in wet bandages.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:	Ŭ
P402 + P404 P405	Store in a dry place. Store in a closed container. Store locked up.
Disposal: P501	Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No further available information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product form

: Manufactured article

Hazardous components

Component	CAS Number	Percent of Total Weight
Organic Carbonate	Not applicable	13-18%
Carbon(Graphite)	7782-42-5	12-15%
Copper Foil	7440-50-8	7-10%
Aluminum Foil	7429-90-5	5%
Nickel	7440-02-0	2-5%
Lithium Salts	Not applicable	1-5%
Lithium Cobalt Oxide	12190-79-3	2-3%

SECTION 4. FIRST AID MEASURES

Under normal conditions of battery use, internal ingredients/components will not present a health hazard. The following information is provided for exposures that may occur during battery production or container breakage or under extreme heat conditions such as fire.

Burning and disassembly batteries may emit acrid smoke, irritating fumes, and toxic fumes of hazardous oxides of carbons, hydrofluoric acid and other toxic by-products.

General advice	 Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Move to fresh air. If breathed in, move person into fresh air. Keep patient warm and at rest.

3/10

Product name: Polymer Lithium-Ion Battery Pack MSDS Number: SDS201712211055 Page: 4 of 10 D09 Revision Date: 14/01/2022 Version: 6.0 If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician. : If on skin, rinse well with water. In case of skin contact Wash contaminated clothing before re-use. : In the case of contact with eyes, rinse immediately with plenty In case of eye contact of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye. If swallowed : Get medical attention immediately. Do NOT induce vomiting. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Most important symptoms : None known and effects, both acute and delayed Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	cumstances and the	sures that are appropriate to local surrounding environment. bon dioxide (CO2)/Dry chemical
media Specific hazards during firefighting	nditions, but it will bu	considered safe under normal use Irn in case of fire. m fire fighting to enter drains or water
Hazardous combustion products	oxic fumes crid smoke/irritating fu	umes
Specific extinguishing methods	oduct is compatible v	vith standard fire-fighting agents.
Further information		aminated fire extinguishing water must dance with local regulations.
Special protective equipment for firefighters		ar self-contained breathing apparatus

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Normally not required.
protective equipment and	In the event of fire and breakage, please ensure that:
emergency procedures	Use personal protective equipment.

4 / 10

Product name: Polymer Lithium-Ion Battery Pack D09 Revision Date: 14/01/2022 Version: 6.0 MSDS Number: SDS201712211055 Page: 5 of 10

Ensure adequate ventilation.
Persons not wearing protective equipment should be excluded
from area of spill until clean-up has been completed.Environmental precautions: Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.Methods and materials for
containment and cleaning up: If possible, carefully neutralize spilled electrolyte with soda
ash, sodium bicarbonate, lime, etc.Other information: Comply with all applicable national and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Use only approved chargers and procedures. Improperly charging a cell may cause the cell or battery to flame or damage. Do not drop battery, puncture, or attempt to open battery case. Avoid contact with the internal components of a battery. Do not subject product to open flame or fire and avoid situations that could cause arcing between terminals. For personal protection see section 8.
Conditions for safe storage	 Store batteries under roof in cool, dry, well-ventilated areas separated from incompatible materials and from activities that may create flames, spark, or heat. Observe label precautions.
Charging	 Shut-off power to chargers whenever not in use and before detachment of any circuit connections. Charging space should be ventilated. There is a possible risk of electric shock from charging equipment and from strings of series connected batteries, whether or not being charged.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Engineering measures	 Store sealed batteries at ambient temperature. Never recharge batteries in an unventilated, enclosed space. Do not subject product to open flame or fire. Avoid conditions that could cause arcing between terminals.
Personal protective equipmen	t
Respiratory protection	NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT.
Hand protection	NONE REQUIRED FOR NORMAL HANDLING OF THE PRODUCT.
Eye protection	NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT.

Product name: Polymer Lithium-Ion Battery Pack D09 Revision Date: 14/01/2022 Version: 6.0 MSDS Number: SDS201712211055 Page: 6 of 10

Skin and body protection	: NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT.
Hygiene measures	: Wash hands before breaks and at the end of workday.
	When using do not eat or drink.
	When using do not smoke.
	When doing do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Manufactured article
Colour	: No data available
Odour	: Odorless
Odour Threshold	: No data available
рН	: Not applicable
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: No data available
Evaporation rate	: No data available
Flammability	: Non flammable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: Not applicable
Relative vapour density	: No data available
Relative density	: No data available
Density	: No data available
Water solubility	: Insoluble in water
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: Not applicable

Product name: Polymer Lithium-Ion Battery Pack D09 Revision Date: 14/01/2022 Version: 6.0 MSDS Number: SDS201712211055 Page: 7 of 10

Viscosity, kinematic	: No applicable	
Oxidizing properties	: No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Non-reactive under normal conditions of use, storage and transport.	
Chemical stability	: Stable under recommended storage conditions.	
	The sealed battery is considered stable.	
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.	
Incompatible materials	: None known.	
Hazardous decomposition products	: None under normal operating conditions. Carbon dioxide and hydrogen fluoride gas may be generated during combustion of battery.	

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

	Acute toxicity		
	Not classified based on availab	le information.	
	Skin corrosion/irritation		
	Not classified based on available information.		
	Serious eye damage/eye irritation		
	Not classified based on available information.		
	Respiratory or skin sensitisation		
	Skin sensitisation: Not classified based on available information.		
	Respiratory sensitisation: Not classified based on available information.		
	Germ cell mutagenicity		
	Not classified based on available information.		
Carcinogenicity			
Not classified based on available information.			
Reproductive toxicity			
Not classified based on available information.			
STOT - single exposure			
Not classified based on available information.			
	STOT - repeated exposure		
Not classified based on available information.			
Aspiration toxicity			
Not classified based on available information.			
	Further information		
	Carcinogenicity:		
	IARC	Cobalt in lithium cobalt oxide is considered as	
		a class 2B carcinogen by IARC.	

Product name: Polymer Lithium-Ion Battery Pack D09 Revision Date: 14/01/2022 Version: 6.0 MSDS Number: SDS201712211055 Page: 8 of 10

OSHA No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

None Known to be human carcinogen

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

When properly used or disposed, the batteries do not present environmental hazards. Do not let internal components enter marine environment. Avoid release to waterways, wastewater or groundwater. **Persistence and degradability** No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice	 This battery should be recycled if possible. The product should not be allowed to enter drains, water courses or the soil. This product must be disposed of in a safe manner. Send to a licensed waste management company. Dispose of in accordance with all applicable national and local regulations.
----------------	---

SECTION 14. TRANSPORT INFORMATION

International transport regulations

Lithium-ion batteries (limited to a maximum of 30% SoC) are subject to the following transport rules:

Method	Technical Guidelines	Packing Instruction and Special
Air	2021-2022 Edition of the ICAO Technical	Packing Instruction 965(PI965,
	Instructions for the Safe Transport of	section IA)
	Dangerous Goods by Air (Technical	IMP: RBI
	Instructions) and the 63rd edition of the IATA	Limit per package:
	Dangerous Goods Regulations (DGR).	Pax A/C = Forbidden
		CAO = 35 kg
Sea	IMDG Code(2020 edition amendmen 40-20)	Special Provision 188, 230, 310, 348, 376, 377,384

Product name: Polymer Lithium-Ion Battery Pack D09 Revision Date: 14/01/2022 Version: 6.0 MSDS Number: SDS201712211055 Page: 9 of 10

Provisions for the international transportation (pursuant to ICAO-TI/IATA-DGR, IMDG Code):UN-No.:UN 3480Proper Shipping Name:Lithium Ion Batteries

IMDG((2020 edition amendmen 40-20))

UN Number	UN3480
UN Proper shipping name	Lithium ion batteries
Transport hazard class(es)	9
Packing Group	N/A

IATA(63rd Edition of the IATA Dangerous Goods Regulations (DGR))

UN Number	UN3480
UN Proper shipping name	Lithium ion batteries
Hazard Class	9
Packing Group	N/A

ADR

UN Number	UN3480
UN Proper shipping name	Lithium ion batteries
Hazard Class	9
Packing Group	N/A



Note: All lithium ion cells and batteries shipped by themselves (UN 3480) are forbidden for transport as cargo on passenger aircraft. All packages prepared in accordance with Packing Instruction 965, Section IA, IB and II, must bear a Cargo Aircraft Only label, in addition to existing marks and/or labels.

SECTION 15. REGULATORY INFORMATION

SARA 302	: Not regulated.	
SARA 311/312 Hazards	: Not regulated.	
SARA 313 Component(s)	: Cobalt compounds are considered hazardous and are subjected to reporting requirements of section 313 title III of the superfund amendments and reauthorization act of 1986 (SARA) and 40 CFR part 372.	
California Prop 65	: This product does not contain any chemical known to the State of California to cause cancer.	
9 / 10		

Product name: Polymer Lithium-Ion Battery Pack D09 Revision Date: 14/01/2022 Version: 6.0 MSDS Number: SDS201712211055 Page: 10 of 10

SECTION 16. OTHER INFORMATION

Further information Revision Date: 14/01/2022

Disclaimer:

This SDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by us to be dependable and is accurate to the best of our knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage or release to the environment. We assumed no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.

End of Report