



Seat Colors
Black Vinyl



Body Color
Red



Roll

**Disassembles
Quickly &
Easily!**

LiteRider[®]ptc

The LiteRider PTC is easier than ever to transport! This new design creates a lightweight base that disassembles into two pieces with the heaviest piece weighing only 35 lbs! Model GP162 offers a compact turning radius with a robust 300 lb. weight capacity. For the consumer looking for high quality at a great value, nothing beats the all-new LiteRider PTC!

Model Number	GP162
Weight Capacity	300 lbs.
Drive Wheels	Rear
Maximum Speed	3.5 mph
Operating Range ¹	9.5 miles
Ground Clearance	2.5"
Turning Radius	26"
Type Batteries	2-18 AH
Colors	Red
Freewheel Mode	Yes
Electronic Speed Control	Yes
Electro-Mechanical Brakes	Yes
Charger	Off Board
Controller	PG VR-2 50 Amp Remote
Dimensions:	
Length	33"
Width	22.5"
Height (ground to top of back of seat)	33" - 34"
Height (ground to top of back of headrest)	N/A
Ground to Top of Seat	20.5" - 21.5"
Number of Seat Height Positions	2
Size of Increments	1.0"
Weight of Unit: (assembled)	
Front Half	34 lbs.
Rear Half	35 lbs.
Seat w/Arms	22 lbs.
Batteries	25 lbs/pack
Tires:	
Drive Wheels	9"
Casters	6"
Anti-Tip Wheels	3"
Standard Seat:	
Slide Seat	N/A
Back Height - no headrest	16"
Back Height with headrest	N/A
Width x Depth	17" x 16"
Color	Black Vinyl
Footrest:	
Height adjustable	Yes
Angle adjustable	Yes
Warranty:	
Frame	Five Years
Drive Train	13 Month Warranty
Electronics ²	13 Month Warranty

¹ Battery range will vary due to rider weight, drive surface and terrain.

² Electronics warranty excludes batteries.

Disassembles easily for transport!



1. Remove seat



2. Pull out battery pack



3. Grasp the frame and locking handle; lift the handle to unlock, and lift the frame up and off the drive train.



Perfect for transport!

Available Accessories:

- Cane Holder Tube
- Oxygen Tank Holder
- Cup Holder
- Quad Cane Holder
- Walker Holder
- Crutch Holder
- Safety Flag
- Power Chair Cover
- Touch-up Paint
- Deluxe Pack N' Go
- Seat Belt (Optional)

Some accessories require a mounting bracket or mounting clips.