



## R Series Trim Vacuums



# Trim Vacuums for Packaging Applications



The R series is specifically designed for use in packaging applications in industries such as food and pharmaceutical. The features of these vacuums make it ideal for removing excess lateral trim and scraps during packaging processes.

- Three-phase regenerative blower allows vacuum to run virtually maintenance-free for long periods of time.
- High vacuum pressure compresses the collected debris to optimize the 30- to 40-gallon collection capacity.
- Equipped with motor protection switch (overload) and pressure relief valve, making the vacuum reliable in continuous duty applications.
- Viewing window indicates when the bag needs to be emptied.
- Mounted on wheels for easy maneuverability.
- Heavy-duty, epoxy-painted steel or stainless steel collection container.
- Container latches provide quick access to the collection tank for easy disposal.
- Quiet operating performance for user comfort.



Technical Features		R104	R154	R155	R305
Voltage @ 60 Hz.	volts	200-240/460*	200-240/460*	200-240/460/575	200-240/460/575
Power	watts	950	1300	2050	2550
Current draw	amps	4/2.3	5/2.6	7.6/4.4/3	10.3/6/4.5
Waterlift, controlled	inches of H2O	64	60	88	82.6
Airflow, blower max	cfm	102	135	150	222
Noise level @ 3'3"	dB(A)	68	72	72	75
Filter area, main filter	sq. ft.	12.38	12.38	15.45	15.45
Machine inlet	mm	50	50	50	50
Tank capacity	gallons	30	30	40	40
Dimensions (Dia x H)	inches	18.11 x 47.24	18.11 x 47.24	22.05 x 49.21	22.05 x 49.21
Weight	lbs.	84	88	104	135
Cord length	feet	20	20	20	20

\* Also available in single-phase power