

T22 - T40 - T40W - T75



The "T" series. A new era in industrial vacuums

Nilfisk-CFM introduces the new standard three phase range



T22



T40



T40W



T75



The new threephase industrial vacuums T22, T40, T40W and T75 for wet & dry materials set a new standard in heavy industry vacuum cleaning.

This new range is equipped with motors from 2,2 up to 7,5 kW, allowing users to choose the most suitable model for the different needs. In particular the 4 kW model is available with double stage side-channel blower connected in series for a greater vacuum (model T40) or connected in parallel for an highest airflow (T40W).

Mechanical, ceramics, food and chemical industries can now rely on industrial vacuums, designed according to their production requirements, for the cleaning and maintenance of the plants. The new vacuums are strong, powerful, essential and designed to work firstly with people and then with processing machines.

Give a shape to your needs

Models T22, T40, T40W and T75 have been designed following the requests of production companies::

- a large filter area for the collection of very fine dust (class "L" and "M" filters)
- HEPA H14 absolute filter to assure a healthier working environment
- big wheels, 2 castors with brakes and an ergonomic handle to easily move the vacuum
- Longopac® to collect the material in an "endless" bag (version GU FM)
- manual filter shaker and manometer to check filter efficiency
- reliable side-channel blower, needing no maintenance

Choosing Nilfisk-CFM means choosing quality, the widest accessories range, the warranty of an international brand and 30 years of experience with manufacturing companies.

Discover the new T models on www.Nilfisk-CFM.it.



Description	T22 L50 T22 L100	T40 L50 T40 L100	T40W L50 T40W L100	T75 L100
Code	4030500075 4030500072	4030500076 4030500073	4030500077 4030500074	4030500117
IP	55	55	55	55
INSULATION CLASS	F	F	F	F
VOLTAGE (kW)	2,2	4,3	4	7,5
TENSIONE (V)	400	400	400	400
FREQUENCY (Hz)	50	50	50	50
SOUND PRESSURE (dB(A) ISO 3744)	68	72	72	74
AIRFLOW WITHOUT HOSE (m³/h)	315	315	516	534
VACUUM MAX (mBar)	300	460	300	430
CAPACITY (l)	50/100	50/100	50/100	100
SIZE (LxWxH mm)	1130x600x1240 1130x600x1530	1130x600x1240 1130x600x1530	1130x600x1240 1130x600x1530	1130x600x1640
WEIGHT (kg)	111/114	132/135	136/139	188



Liquid cut-off on model T40



Manometer



HEPA absolute filter on model T40W



Longopac®